

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: .45823
Product Name: WOODMASTER SEMI-SOLID STAIN - 53 BASE
Revision Date: Nov 15, 2023 **Date Printed:** Nov 15, 2023
Version: 1.0 **Supersedes Date:** N.A.
Manufacturer's Name: Repolite Paints, Inc.
Address: 473 West 17th Street Holland, MI, US, 49423
Emergency Phone: 800-535-5053
Information Phone Number: 616-396-1275
Fax: 616-396-9654

SECTION 2) HAZARDS IDENTIFICATION

Classification

Flammable Liquids - Category 2
Flammables solids - Category 2
Aspiration Hazard - Category 1
Carcinogenicity - Category 1A
Eye Irritation - Category 2
Germ Cell Mutagenicity - Category 1B
Skin Irritation - Category 3
Skin Sensitizer - Category 1
Specific Target Organ Toxicity - Repeated Exposure - Category 1
Acute aquatic toxicity - Category 2
Chronic aquatic toxicity - Category 2

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H225 - Highly flammable liquid and vapor
H228 - Flammable solid

Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways

- H350 - May cause cancer
- H319 - Causes serious eye irritation
- H340 - May cause genetic defects.
- H316 - Causes mild skin irritation
- H317 - May cause an allergic skin reaction
- H372 - Causes damage to organs through prolonged or repeated exposure.

Hazardous Statements - Environmental

- H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements - General

- P101 - If medical advice is needed, have product container or label at hand.
- P102 - Keep out of reach of children.
- P103 - Read label before use.

Precautionary Statements - Prevention

- P273 - Avoid release to the environment.
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P280 - Wear protective gloves, protective clothing, eye protection/face protection.
- P264 - Wash thoroughly after handling.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 - Keep container tightly closed.
- P240 - Ground/bond container and receiving equipment.
- P241 - Use explosion-proof electrical/ventilating/lighting equipment.
- P242 - Use only non-sparking tools.
- P243 - Take action to prevent static discharges.
- P272 - Contaminated work clothing should not be allowed out of the workplace.
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
- P270 - Do not eat, drink or smoke when using this product.

Precautionary Statements - Response

- P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
- P331 - Do NOT induce vomiting.
- P308 + P313 - IF exposed or concerned: Get medical advice/attention.
- P391 - Collect spillage.
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 - If eye irritation persists: Get medical advice/attention.
- P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P370 + P378 - In case of fire: Use dry chemical, foam, or carbon dioxide to extinguish.
- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.
- P321 - For specific treatment see section 4.
- P362 + P364 - Take off contaminated clothing. And wash it before reuse.
- P314 - Get Medical advice/attention if you feel unwell.

Precautionary Statements - Storage

- P405 - Store locked up.
- P403 + P235 - Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Acute toxicity of less than one percent of the mixture is unknown

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0064741-65-7	ODORLESS MINERAL SPIRITS	28% - 47%
0013463-67-7	TITANIUM DIOXIDE	3% - 7%
0001314-13-2	ZINC OXIDE	1.6% - 4%
0061790-53-2	DIATOMACEOUS EARTH, INHALABLE PARTICULATE	1.3% - 3%
0001335-30-4	ALUMINUM SILICATE HYDRATE	0.1% - 1.2%
0007631-86-9	SILICA, AMORPHOUS	0.0% - 0.8%
0008052-41-3	STODDARD SOLVENT	0.0% - 0.6%
0000577-11-7	DI-2-ETHYLHEXYL SODIUM SULFOSUCCINATE	0.0% - 0.4%
0055406-53-6	3-IODO-2-PROPYNYL BUTYLCARBAMATE	0.0% - 0.3%
0000136-51-6	CALCIUM 2-ETHYLHEXANOATE	0.0% - 0.2%
0000330-54-1	DIURON	0.0% - 0.2%
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	Trace
0000108-38-3	M-XYLENE	Trace
0001314-23-4	ZIRCONIA OXIDE	Trace
0064742-94-5	AROMATIC HYDROCARBON MIXTURE >C9	Trace
0064742-48-9	NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	Trace
0000111-46-6	DIETHYLENE GLYCOL	Trace
0000095-63-6	1,2,4-TRIMETHYLBENZENE	Trace
0000100-41-4	ETHYLBENZENE	Trace
0000106-42-3	P-XYLENE	Trace
0000095-47-6	O-XYLENE	Trace
0000107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	Trace
0064742-88-7	MEDIUM MINERAL SPIRITS	Trace
0012001-85-3	ZINC NAPHTHANATE	Trace
0000108-67-8	MESITYLENE	Trace
0000104-76-7	2-ETHYL-1-HEXANOL	Trace
0064742-89-8	ALIPHATIC, LIGHT HYDROCARBON SOLVENT	Trace
0000136-53-8	zinc 2-ethylhexanoate	Trace
0000142-16-5	2-Butenedioic acid (2Z)-, 1,4-bis(2-ethylhexyl) ester	Trace
0014808-60-7	SILICA, CRYSTALLINE	Trace
0000091-20-3	NAPHTHALENE	Trace
0007631-90-5	SODIUM BISULFITE	Trace
0025340-17-4	DIETHYLBENZENE	Trace
0000098-82-8	CUMENE	Trace

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Eliminate all ignition sources if safe to do so.

Skin Contact

Take off all contaminated clothing, shoes, and leather goods (e.g., watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation or rash occurs: Get medical advice/attention.

Store contaminated clothing under water and wash before re-use (or discard).

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion

Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, or carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Unsuitable Extinguishing Media

No data available.

Specific Hazards in Case of Fire

Vapors are heavier than air and may travel along the ground to ignition sources at locations distant from material handling point.

Vapor accumulations and spray mist may flash or explode if ignited.

Closed containers may rupture due to pressure buildup when exposed to extreme heat.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Dike area to contain spill.

Absorb spill with inert absorbent.

SECTION 7) HANDLING AND STORAGE

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced.

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

A suitable, NIOSH-approved respirator and goggles should be worn when sanding or grinding objects coated with this paint.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	ACGIH TWA (ppm)
1,2,4-TRIMETHYLBENZENE								10
2-ETHYL-1-HEXANOL								5
ALIPHATIC, LIGHT HYDROCARBON	500	2000			1			(L)[N159](L)[N800]

N SOLVENT								
ALUMINUM SILICATE HYDRATE								
AROMATIC HYDROCARBON MIXTURE >C9	500	2000		1				(L)[N159](L)[N800]
CUMENE	50	245		1		1		5
DIATOMACEOUS EARTH, INHALABLE PARTICULATE	20 (a) mppfc	80 mg/m3 percent SiO2		1,3				
DIURON								
ETHYLBENZENE	100	435		1				20
MEDIUM MINERAL SPIRITS								(L)[N159](L)[N800]
MESITYLENE								10
M-XYLENE	100	435		1				20
NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	500	2000		1				(L)[N159](L)[N800]
NAPHTHALENE	10	50		1				10
ODORLESS MINERAL SPIRITS	500	2000		1				(L)
O-XYLENE	100	435		1				20
PROPYLENE GLYCOL MONOMETHYL ETHER								50
P-XYLENE	100	435		1				20
SILICA, AMORPHOUS	20 (b)	80 mg/m3 percent SiO2+2		1,3				
SILICA, CRYSTALLINE	a	[10 mg/m3 percent SiO2+2 / 250 percent SiO2+5 mppcf]; [30 mg/m3 percent SiO2+2];		[1,3]; [3];				
SODIUM BISULFITE								
STODDARD SOLVENT	500	2900		1				100
TITANIUM DIOXIDE		15		1				
ZINC OXIDE		[15]; [5];		1				
ZIRCONIA OXIDE		5		1				

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
1,2,4-TRIMETHYLBE				A4		CNS impair; hematologic eff

NZENE						
2-ETHYL-1-HEXANOL				A3	A3	URT & eye irr
ALIPHATIC, LIGHT HYDROCARBON SOLVENT	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			[A2][N159]A2[N800]]; [A4][N159]A4[N800]];	[A2][N159]A2[N800]]; [A4][N159]A4[N800]];	URT irr [N159]URT irr [N800]
ALUMINUM SILICATE HYDRATE	1 (R)			A4	A4	Pneumoconiosis; LRT irr; neurotoxicity
AROMATIC HYDROCARBON MIXTURE >C9	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			[A2][N159]A2[N800]]; [A4][N159]A4[N800]];	[A2][N159]A2[N800]]; [A4][N159]A4[N800]];	URT irr [N159]URT irr [N800]
CUMENE				A3	A3	URT adenoma; neurological eff
DIATOMACEOUS EARTH, INHALABLE PARTICULATE						
DIURON	10			A4	A4	URT irr
ETHYLBENZENE				A3	OTO;BEI	URT & eye irr; ototoxicity; kidney eff; CNS impair
MEDIUM MINERAL SPIRITS	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			[A2][N159]A2[N800]]; [A4][N159]A4[N800]];	[A2][N159]A2[N800]]; [A4][N159]A4[N800]];	URT irr [N159]URT irr [N800]
MESITYLENE						CNS impair; hematologic eff
M-XYLENE						Eye irr & URT irr, hemotologic effects; CNS impair
NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			[A2][N159]A2[N800]]; [A4][N159]A4[N800]];	[A2][N159]A2[N800]]; [A4][N159]A4[N800]];	URT irr [N159]URT irr [N800]
NAPHTHALENE				A3	Skin; A3; BEI	URT irr; cataracts; hemolytic anemia
ODORLESS MINERAL SPIRITS	[(L)]; [5 (I)];			[A2]; [A4];	[A2]; [A4];	URT irr
O-XYLENE						Eye irr & URT irr, hemotologic effects; CNS impair
PROPYLENE GLYCOL MONOMETHYL ETHER		100		A4	A4	Eye & URT irr
P-XYLENE				A4		Eye irr & URT irr, hemotologic effects; ototoxicity; CNS impair
SILICA, AMORPHOUS						
SILICA, CRYSTALLINE	0.025 (R)			A2	A2	Pulmonary fibrosis; lung cancer
SODIUM BISULFITE	5			A4	A4	Skin; eye, & URT irr

STODDARD SOLVENT	[(L)]; [5 (I)];			[A2]; [A4];	[A2]; [A4];	Eye, skin, & kidney dam; nausea; CNS impair
TITANIUM DIOXIDE	0.2 (R)(Nano), 2.5 (R)			A3		LRT irr; pneumoconiosis
ZINC OXIDE	2 (R)		10 (R)			Metal fume fever
ZIRCONIA OXIDE	5		10	A4	A4	Resp irr

LRT - Lower respiratory tract, A2 - Suspected Human Carcinogen, dam - Damage, (R) - Respirable fraction, eff - Effects, A4 - Not Classifiable as a Human Carcinogen, (C) - Ceiling limit, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, CNS - Central nervous system, irr - Irritation, (L) - Exposure by all routes should be carefully controlled to levels as low as possible, URT - Upper respiratory tract, BEI - Substances for which there is a Biological Exposure Index or Indices, resp - respiratory, impair - Impairment

The information in this Section does not list non-hazardous components that might have relevant ACGIH TWA (mg/m3), ACGIH STEL (mg/m3), ACGIH Carcinogen, ACGIH Notations, ACGIH TLV Basis, OSHA TWA (mg/m3), OSHA Tables (Z1, Z2, Z3) regulatory values, if they are present at less than 10%. Please contact manufacturer for more information.

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	9.00613 lb/gal
% Solids By Weight	60.57580%
% VOC	38.70920%
Density VOC	3.48620 lb/gal
VOC Regulatory	3.48086 lb/gal
VOC Regulatory	417.11100 g/l

Appearance	N/A
Odor Threshold	N/A
Odor Description	N/A
pH	N/A
Water Solubility	N/A
Flammability	N/A
Flash Point Symbol	N/A
Flash Point	N/A
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	NA
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N/A
Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

Chemical Stability

Stable.

Possibility of Hazardous Reactions/Polymerization

No data available.

Conditions To Avoid

Excessive heat.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

May produce fumes when heated to decomposition.

Fumes may contain carbon monoxide and carbon dioxide.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

Causes mild skin irritation

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the skin.

0000111-46-6 DIETHYLENE GLYCOL

May cause mild skin irritation.

Serious Eye Damage/Irritation

Causes serious eye irritation

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the eyes.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Vapor is a mild eye irritant.

Respiratory/Skin Sensitization

May cause an allergic skin reaction

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the respiratory tract.

Germ Cell Mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer

Reproductive Toxicity

Based on available data, the classification criteria are not met.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The NOAEL for paternal toxicity is 300 ppm and for offspring toxicity is 1000 ppm. The NOAEL for maternal and fetotoxicity was considered to be 1500 ppm. Effects appear secondary to parental weight loss.

Specific Target Organ Toxicity - Single Exposure

Based on available data, the classification criteria are not met.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Exposure to very high concentrations could cause depression of the central nervous system.

0000111-46-6 DIETHYLENE GLYCOL

Ingestion may cause effects on the central nervous system, the liver, and the kidneys (including kidney impairment).

Specific Target Organ Toxicity - Repeated Exposure

Causes damage to organs through prolonged or repeated exposure.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance defats the skin, which may cause dryness or cracking. Prolonged exposure to vapors may cause coughing, shortness of breath, dizziness and intoxication.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

Aspiration Hazard

May be fatal if swallowed and enters airways

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

If liquid is swallowed, it may get into lungs by aspiration

Acute Toxicity

Based on available data, the classification criteria are not met.

0000111-46-6 DIETHYLENE GLYCOL

Ingestion can lead to death.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Inhalation of high concentrations can cause CNS depression; Ingestion can cause aspiration into the lungs.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

High concentration of vapors may cause intoxication

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance can be absorbed into the body by inhalation of its aerosol or vapour, through the skin and by ingestion.

0000111-46-6 DIETHYLENE GLYCOL

Ingestion.

Chronic Exposure

0000098-82-8 CUMENE

TERATOGENIC EFFECTS: Cumene has been Classified as POSSIBLE for humans.

0000100-41-4 ETHYLBENZENE

CARCINOGENIC EFFECTS: Ethyl Benzene has been listed by IARC as Group 2B, Possibly Carcinogenic to Humans.

TERATOGENIC EFFECTS: Ethyl Benzene has been Classified as POSSIBLE for humans.

0014808-60-7 SILICA, CRYSTALLINE

Prolonged inhalation of respirable crystalline silica dust can result in lung disease (i.e. silicosis and/or lung cancer). Symptoms include coughing, shortness of breath, wheezing and reduced pulmonary function.

Potential Health Effects - Miscellaneous

0000091-20-3 NAPHTHALENE

Is an IARC, NTP or OSHA carcinogen. Tests in some laboratory animals demonstrate carcinogenic activity. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: kidneys, liver. Recurrent overexposure may result in liver and kidney injury. WARNING: This chemical is known to the State of California to cause cancer.

0000100-41-4 ETHYLBENZENE

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Tests in laboratory animals have shown effects on any of the following organs/systems: kidneys, liver. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

0013463-67-7 TITANIUM DIOXIDE

Is an IARC, NTP or OSHA carcinogen. In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m³ respirable titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was

overwhelmed and that the results at the massive 250 mg/m³ level are not relevant to the workplace. 'Results of a DuPont epidemiology study showed that employees who had been exposed to Titanium Dioxide were at no greater risk of developing lung cancer than were employees who had not been exposed to Titanium dioxide. No pulmonary fibrosis was found in any of the employees and no association was observed between Titanium dioxide exposure and chronic respiratory disease or x-ray abnormalities. Based on the results of this study DuPont concludes that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.'

0014808-60-7 SILICA, CRYSTALLINE

Is an IARC, NTP or OSHA carcinogen. Repeated overexposure to crystalline silica may lead to x-ray changes and chronic lung disease. Inhalation of high dust concentrations may cause: breathing difficulties, lung injury. WARNING: This chemical is known to the State of California to cause cancer.

0064741-65-7 ODORLESS MINERAL SPIRITS

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-88-7 MEDIUM MINERAL SPIRITS

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. This substance may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, lungs, reproductive system, skin. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-89-8 ALIPHATIC, LIGHT HYDROCARBON SOLVENT

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-95-6 AROMATIC HYDROCARBON MIXTURE >C9

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0000091-20-3 NAPHTHALENE

LC50: Insufficient data

LD50 (oral, mouse): 533 mg/kg (male); 710 mg/kg (female) (1)

LD50 (oral, rat): 1780 mg/kg (2)

0000095-47-6 O-XYLENE

LC50 (rat): 5300 ppm (4-hour exposure); cited as 4330 ppm (6-hour exposure) (3)

LC50 (mouse): 5630 ppm (4-hour exposure); cited as 4595 ppm (6-hour exposure) (3,4)

LD50 (oral, rat): 3608 mg/kg (3,16)

LD50 (dermal, rabbit): 20000 mg/kg (3)

0000095-63-6 1,2,4-TRIMETHYLBENZENE

LC50 (rat): 18 g/m³ (4-hour exposure) (1)

LD50 (oral, rat): 5 g/kg (1)

0000098-82-8 CUMENE

LC50 (inhalation, mouse): 10 mg/L; (2000 ppm); 7-hr exposure (1,3)

LC50 (inhalation, rat): 39 mg/L (8000 ppm); 4-hr exposure (1,3,6)

LD50 (oral, rat): Reported as 1.4 g/kg and 2.26 g/kg (1,3,4)

LD50 (skin, rabbit): 10627 mg/kg (4)

0000100-41-4 ETHYLBENZENE

LC50 (inhalation, rat): 4000 ppm; 4-hour exposure (3)

LD50 (oral, rat): 3.5 g/kg (1,3,5,10)

LD50 (oral, rat): 4.72 g/kg (3,5,7,8)

LD50 (dermal, rabbit): 17.8 g/kg (11)

0000106-42-3 P-XYLENE

LC50 (rat): 4740 ppm (4-hour exposure) (3)

LC50 (mouse): 4800 ppm (4-hour exposure); cited as 3900 ppm (6-hour exposure) (1,4,6)

LD50 (oral, rat): 4030 mg/kg (3); 4550 mg/kg (10)

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

LC50 (rat): 15000 ppm; 4-hr exposure (2)

LC50 (guinea pig): 15000 ppm; 10-hr exposure (2)

LD50 (oral, rat): 6.6 g/kg (5.2-7.5 g/kg) (10)

LD50 (oral, mouse): 10.7-10.8 g/kg (2,12)

LD50 (oral, dog): 4.6-5.5 g/kg (2); approximately 9.2 g/kg (2)

LD50 (oral, rabbit): 5.2-5.3 g/kg (2,12)

LD50 (dermal, rabbit): 13-14 g/kg (10)

0000108-38-3 M-XYLENE

LC50 (rat): 7330 ppm (4-hour exposure); cited as 5984 ppm (6-hour exposure) (3,17)

LC50 (mouse): 6450 ppm (4-hour exposure); cited as 5267 ppm (6-hour exposure) (3)

LD50 (oral, rat): 5011 mg/kg (3); 6660 mg/kg (3)

LD50 (dermal, rabbit): 12180 mg/kg (3,17)

0000108-67-8 MESITYLENE

LC50 (rat): 24 g/m3 (4-hour exposure) (2)

0001314-13-2 ZINC OXIDE

LD50 (oral, mouse): 7950 mg/kg body weight (9)

0008052-41-3 STODDARD SOLVENT

LC50 (rat): greater than 5500 mg/m3 (880 ppm) (whole body exposure for 4 hours) (1)

LC50 (rat): greater than 8200 mg/m3 (1300 ppm) (2)

LD50 (oral, rat): greater than 5 g/kg (1)

LD50 (dermal, rabbit): greater than 3 g/kg (1)

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

LC50 (Rodent - rat, Inhalation) : >590 mg/m3 (4 hour exposure) Toxic effects : Details of toxic effects not reported other than lethal dose value.

LD50 (Rodent - rabbit, Administration onto the skin) : >2 mL/kg ,Toxic effects : Behavioral - somnolence (general depressed activity) Behavioral - changes in motor activity (specific assay) Behavioral - irritability

0000330-54-1 DIURON

LD50 (oral, rodent - rat): 1017 mg/kg, Toxic effects : Behavioral - general anesthetic Behavioural - ataxia

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Toxic to aquatic life

Toxic to aquatic life with long lasting effects

0000330-54-1 DIURON

LC50(Fish - Pimephales Promelas , 96 hrs) : 2.7971664 mg/L

EC50(Algae - Synechococcus sp. , 72 hrs) : 0.00055 mg/L EC50(Crustaceans - Mesocyclops aspericornis, 48 hrs) : > 0.677 mg/L

0001314-13-2 ZINC OXIDE

LC50 (Crustacean - Daphnia magna, 48 hrs) : 0.098 mg/l, type of exposure : static

Persistence and Degradability

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Readily biodegradable in water. Half-life in air = 3.1 hours.

0000111-46-6 DIETHYLENE GLYCOL

Readily biodegradable.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Readily biodegradable

Bioaccumulative Potential

0000111-46-6 DIETHYLENE GLYCOL

Bioaccumulation is not expected.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Has the potential to bioaccumulate.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance is not PBT / vPvB.

0000111-46-6 DIETHYLENE GLYCOL

The substance is not PBT / vPvB.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II

IMDG Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II
Marine Pollutant : No data available

IATA Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II

SECTION 15) REGULATORY INFORMATION

REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0064741-65-7	ODORLESS MINERAL SPIRITS	28% - 47%	DSL, SARA312
0091313-01-8	Non-Hazardous, Solid	16% - 27%	DSL, SARA312
0037244-96-5	NEPHELINE SYENITE	11% - 26%	DSL, SARA312
0013463-67-7	TITANIUM DIOXIDE	3% - 7%	DSL, SARA312, CA_Carcinogen, CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer
0001314-13-2	ZINC OXIDE	1.6% - 4%	SARA313, Canada_NPRI, DSL, SARA312
0061790-53-2	DIATOMACEOUS EARTH, INHALABLE PARTICULATE	1.3% - 3%	SARA312
0001335-30-4	ALUMINUM SILICATE HYDRATE	0.1% - 1.2%	DSL, SARA312
0007631-86-9	SILICA, AMORPHOUS	0.0% - 0.8%	DSL, SARA312
0008052-41-3	STODDARD SOLVENT	0.0% - 0.6%	Canada_NPRI, DSL, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000577-11-7	DI-2-ETHYLHEXYL SODIUM SULFOSUCCINATE	0.0% - 0.4%	DSL, SARA312
0055406-53-6	3-iodo-2-propynyl butylcarbamate	0.0% - 0.3%	SARA313, DSL, SARA312
0000136-52-7	COBALT OCTATE	0.0% - 0.2%	SARA313, Canada_NPRI, DSL, HAPS, SARA312
0000136-51-6	CALCIUM 2-ETHYLHEXANOATE	0.0% - 0.2%	DSL, SARA312
0000330-54-1	DIURON	0.0% - 0.2%	SARA313, DSL, SARA312, CA_Carcinogen, CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	Trace	Canada_NPRI, DSL, SARA312
0000108-38-3	M-XYLENE	Trace	SARA313, Canada_NPRI, DSL, HAPS, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0001314-23-4	ZIRCONIA OXIDE	Trace	DSL, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0064742-94-5	AROMATIC HYDROCARBON MIXTURE >C9	Trace	Canada_NPRI, DSL, SARA312
0064742-48-9	NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	Trace	Canada_NPRI, DSL, SARA312
0000111-46-6	DIETHYLENE GLYCOL	Trace	DSL, SARA312
0000095-63-6	1,2,4-TRIMETHYLBENZENE	Trace	SARA313, Canada_NPRI, DSL, SARA312
0000100-41-4	ETHYLBENZENE	Trace	SARA313, Canada_NPRI, DSL, HAPS, SARA312, CA_Carcinogen, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS, CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer
0000106-42-3	P-XYLENE	Trace	SARA313, Canada_NPRI, DSL, HAPS, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000095-47-6	O-XYLENE	Trace	SARA313, Canada_NPRI, DSL, HAPS, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	Trace	Canada_NPRI, DSL, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0064742-88-7	MEDIUM MINERAL SPIRITS	Trace	Canada_NPRI, DSL, SARA312
0012001-85-3	ZINC NAPHTHANATE	Trace	SARA313, Canada_NPRI, DSL, SARA312
0000108-67-8	MESITYLENE	Trace	Canada_NPRI, DSL, SARA312

0000104-76-7	2-ETHYL-1-HEXANOL	Trace	DSL, SARA312
0064742-89-8	ALIPHATIC, LIGHT HYDROCARBON SOLVENT	Trace	Canada_NPRI, DSL, SARA312
0000136-53-8	zinc 2-ethylhexanoate	Trace	Canada_NPRI, DSL, SARA312
0000142-16-5	2-Butenedioic acid (2Z)-, 1,4-bis(2-ethylhexyl) ester	Trace	DSL, SARA312
0014808-60-7	SILICA, CRYSTALLINE	Trace	DSL, SARA312, CA_Carcinogen, CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer
0000091-20-3	NAPHTHALENE	Trace	SARA313, Canada_NPRI, DSL, HAPS, SARA312, CA_Carcinogen, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS, CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer
0007631-90-5	SODIUM BISULFITE	Trace	DSL, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0025340-17-4	DIETHYLBENZENE	Trace	DSL, SARA312
0000098-82-8	CUMENE	Trace	Canada_NPRI, DSL, HAPS, SARA312, CA_Carcinogen, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS, CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer

The information in this Section does not list non-hazardous components that might have relevant DSL, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS, Canada_NPRI, DSL, SARA312 regulatory values, if they are present at less than 10%. Please contact manufacturer for more information.



WARNING:This product can expose you to chemicals including TITANIUM DIOXIDE, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16) OTHER INFORMATION

Other Special Consideration

* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS.

General

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	/ 2
FLAMMABILITY	2
Physical Hazard	0
Personal Protection	X

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.