

### DESCRIPTION and USES

This 100% Acrylic enamel is a true alternative to conventional alkyd enamels. It offers the application properties, ease of clean up, fast dry and low odor found in latex-based paints. This enamel will provide a durable, stain resistant and washable finish on interior surfaces and a highly weather resistant and color retentive protective coating on exterior surfaces. It has very good wet and dry adhesion to most clean, paintable surfaces. The very low solvent content reduces environmental and human health risks. This product is not intended to be used in corrosive atmospheres or for immersion service. It should be used on properly primed surfaces and should not be considered to be self-priming. This product meets VOC requirements for use in LEED construction.

### SURFACE PREPARATION

Surfaces to be painted must be dry, free of dirt, dust and oil. Unpainted surfaces must be primed with the recommended primer. Smooth all rough surfaces with sandpaper to enhance finish appearance. To ensure adhesion, scuff sand old, alkyd gloss enamel painted surfaces.

### APPLICATION

Application may be made with a brush, roller or airless spray. Maintain a wet edge to minimize lapping. Do not apply at temperatures below 60°F. High humidity will lengthen dry time for recoating and hardness development.

### SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

### COLORS

This product is available in white, RepcoLite's *Color Folio* and *Color Studio* colors, and in OSHA Safety Red and Yellow.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

### TECHNICAL DATA

<b>Finish:</b>	Medium Gloss
<b>Vehicle Type:</b>	100% Acrylic Latex
<b>Pigments:</b>	Titanium Dioxide
<b>Volume Solids:</b>	35%
<b>Coverage:</b>	400 – 450 SF/Gallon
<b>Dry Time:</b>	
<i>Touch:</i>	30 Minutes
<i>Recoat:</i>	2 Hours
<i>Full Hardness:</i>	72 Hours
<b>Primer:</b>	
<i>Masonry:</i>	44610 Sprayable Block Filler
<i>Drywall:</i>	44410 Quick Sealer
<i>Plaster:</i>	44110 Prime-All WB Primer
<i>Non-Ferrous Metals:</i>	44810 QD Rust Inhibitive Primer
<i>Ferrous Metals:</i>	44917 Metl-Clad Metal Primer
<i>Wood (Exterior):</i>	44510 Zip Prime-WB
<i>Wood (Interior):</i>	44010 Pro-Flo Primer-Undercoater 44110 Prime-All WB Primer
<b>VOC:</b>	149 g/l
<b>Clean Up:</b>	Water

### PRODUCT CODE INFORMATION

40910	Glo-Enamel-WB Gloss White
40903	Glo-Enamel-WB 243 Base
40906	Glo-Enamel-WB 246 Base
40920	Glo-Enamel-WB Bright Red
40960	Glo-Enamel-WB Safety Yellow

#### RepcoLite Paints, Inc.

473 W. 17<sup>th</sup> St.

Holland, MI 49423

(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)