

### DESCRIPTION and USES

This product is an acrylic latex paint in a satin sheen designed for use on interior trim, doors and millwork. It is an economical, fast drying, hard and durable coating that resists wear and tear and frequent cleanings. Ideally suited for new construction, this paint is optimized for spray application. However, it may also be applied by brush and roller and can be used over existing coatings, often without the need for a primer.

### SURFACE PREPARATION

All surfaces to be primed must be dry and free of dust and dirt, oil or other contamination. Loose and peeling paint must be removed to provide a sound surface. Patching and caulking should be done prior to painting. Prime all unpainted surfaces if necessary with a suitable primer.

### APPLICATION

Apply using airless spray. Use a .015 - .017 tip, adjusting pressure as needed. Most surfaces will require two coats to achieve a uniform appearance and maximum durability. Allow at least two hours of dry time between coats. For best results apply at a maximum spread rate of 400 square feet per gallon. Do not apply at temperatures below 55°F.

### SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET (SDS) for this product.

### COLORS

White and light colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

### TECHNICAL DATA

<b>Vehicle Type:</b>	Acrylic Latex
<b>Density:</b>	10.8 lb/gal
<b>Weight Solids:</b>	46.2%
<b>Volume Solids:</b>	30.3%
<b>Coverage:</b>	300 – 400 SF/Gallon depending on surface porosity
<b>Dry Time:</b>	
<i>Touch:</i>	30 Minutes
<i>Recoat:</i>	2 Hours
	Allow additional dry time in humid conditions
<b>Primer:</b>	
<i>Drywall:</i>	44310 ELEMENTS Latex Wall Primer 44410 Quick Seal
<i>Plaster:</i>	44110 Prime-All 44313 Quick Sand
<i>Masonry:</i>	44610 Block Filler
<i>Wood:</i>	44110 Prime-All 44010 Pro Flo Primer Undercoater
<i>Steel:</i>	44917 Metl-Clad Gray Metal Primer
<b>VOC:</b>	48 g/l
<b>Clean Up:</b>	Water

### PRODUCT CODE INFORMATION

41111 ELEMENTS Latex Satin Sheen Trim White