

### DESCRIPTION and USES

**Woodmaster Oil Base Semi-Transparent Stain** enhances the grain and texture of the wood surfaces to which it is applied. It penetrates deeply into the wood to provide lasting protection from sun and moisture. Ideal for both horizontal and vertical surfaces constructed of redwood, cedar or treated lumber. Not recommended for fir plywood.

### PREPARATION

**Surface Preparation:** All cutting, gluing, and sanding of the wood should be done before coating. Surfaces to be stained must clean, dry, and free of contaminants such as dirt, oil or wax. If mildew is present, clean the surface with a 50% solution of household bleach and water. New pressure-treated wood should be allowed to dry for at least 30 days. New cedar should have the mill glaze removed through sanding or an oxalic acid-based cleaning/brightener product. Discoloration can be removed and the wood restored to its natural color by using a wood brightener. Rinse well after these treatments. Wear protective gloves, clothing, and goggles when working with bleach or wood brightener. Power washing to remove old or peeling stain is recommended. Allow 2 days for wood to dry after rain, rinsing, or power washing before staining.

### APPLICATION

Stir thoroughly before and occasionally during use. Stains are best applied with a natural bristle brush, paint pad, or special stain applicator. Maintain a wet edge by staining only a few boards at a time. Use as supplied. Do not thin.

### SAFETY INFORMATION

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

### TECHNICAL DATA

<b>Finish:</b>	Semi-Transparent Stain
<b>Vehicle Type:</b>	Soya Alkyd Resins and Linseed Oil
<b>Volume Solids:</b>	31%
<b>Coverage:</b>	150 – 300 SF/Gallon (depending on surface porosity).
<b>Dry Time:</b>	
<i>Touch:</i>	8 Hours
<b>Primer:</b>	
<i>Wood:</i>	Self Prime
<b>VOC:</b>	Less than 550 g/l
<b>Clean Up:</b>	Paint Thinner (Mineral Spirits)

### COLORS

A full range of custom colors are available.

### PRODUCT CODE INFORMATION

45809	Woodmaster Oil Base Semi-Transparent Stain - #9 Base
-------	---

**RepcoLite Paints, Inc.**

473 W. 17<sup>th</sup> St.

Holland, MI 49423

(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)