

DESCRIPTION and USES

Mira Tru-Hue Interior Wiping Stain is designed to produce clear, true colors on wood trim, cabinets, furniture, floors, and paneling. A large selection of standard colors is available, along with an almost limitless selection of special tinted colors. **Mira Tru-Hue Interior Wiping Stain** will not raise the grain of the wood. It has a sealing action that provides an excellent base for finish coats.

SURFACE PREPARATION

All wood surfaces to be finished must be clean, dry, and free of contaminants such as oil or wax. New wood should be dry, clean, and sanded smooth with 120 grit sandpaper. Soft woods may be sealed with **Mira Pre-Stain Interior Softwood Sealer** to improve color uniformity.

For previously finished wood, remove all old finish with paint and varnish remover and sand thoroughly with 120 grit sandpaper.

APPLICATION

Material Preparation: Stir well before and during use. Thinning of this product may result in non-compliance with local, state, or federal VOC regulations.

Application: Apply generously with a brush or cloth. Allow to penetrate up to 5 minutes. Wipe off excess in the direction of the grain with a soft, absorbent cloth. Allow 24 hours dry time before application of finish. Do not thin this product.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Vehicle Type:	Alkyd Resin, Linseed Oil
Volume Solids:	31%
Coverage:	500 – 600 SF/Gallon
Dry Time:	24 hours before finishing (Heavy application may require 48 hours)
VOC:	Less than 550 g/L
Clean Up:	Mineral Spirits (Paint Thinner)

PRODUCT CODE INFORMATION

814	Mira Tru-Hue Interior Wiping Stain
-----	------------------------------------

COLORS

May be tinted to a full range of custom colors using alkyd colorant. Maximum tint load: 16 Fl Oz per gallon.

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com