

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: .322140
Product Name: PREMIUM AEROSOL - SAFETY GREEN
Revision Date: May 24, 2024 **Date Printed:** May 24, 2024
Version: 1.0 **Supersedes Date:** N.A.
Manufacturer's Name: Repolite Paints, Inc.
Address: 473 West 17th Street Holland, MI, US, 49423
Emergency Phone: 800-535-5053
Information Phone Number: 616-396-1275
Fax: 616-396-9654
Product/Recommended Uses:

SECTION 2) HAZARDS IDENTIFICATION

Classification

Aerosols - Category 1
Gases Under Pressure Liquefied Gas
Acute toxicity Oral - Category 5
Aspiration Hazard - Category 1
Carcinogenicity - Category 1A
Eye Irritation - Category 2
Germ Cell Mutagenicity - Category 1B
Reproductive Toxicity - Category 2
Skin Irritation - Category 2
Skin Sensitizer - Category 1
Specific Target Organ Toxicity - Repeated Exposure - Category 1
Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3
Acute aquatic toxicity - Category 3
Chronic aquatic toxicity - Category 3

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H280 - Contains gas under pressure; may explode if heated

Hazardous Statements - Health

H303 - May be harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H350 - May cause cancer
H319 - Causes serious eye irritation
H340 - May cause genetic defects.
H361 - Suspected of damaging fertility or the unborn child
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H372 - Causes damage to organs through prolonged or repeated exposure.
H336 - May cause drowsiness or dizziness

Hazardous Statements - Environmental

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements - Prevention

P273 - Avoid release to the environment.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves, protective clothing, eye protection/face protection.
P264 - Wash thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P233 - Keep container tightly closed.

Precautionary Statements - Response

P312 - Call a POISON CENTER/doctor if you feel unwell.
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331 - Do NOT induce vomiting.
P308 + P313 - IF exposed or concerned: Get medical advice/attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P321 - For specific treatment see section 4.
P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.

P314 - Get Medical advice/attention if you feel unwell.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P405 - Store locked up.

P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

P403 + P405 - Store in a well-ventilated place. Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Hazards Not Otherwise Classified (HNOC)

None known.

Acute toxicity of 23.94% of the mixture is unknown

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0000067-64-1	ACETONE	22% - 27%
proprietary	ALKYD RESIN	16% - 22%
0000108-88-3	TOLUENE	8% - 10%
0000108-38-3	M-XYLENE	5% - 7%
0000074-98-6	PROPANE	4% - 6%
0000106-97-8	BUTANE	4% - 6%
NA-Repcolite	ALKYD RESIN	4% - 5%
0000078-93-3	METHYL ETHYL KETONE	3% - 4%
0000141-78-6	ETHYL ACETATE	3% - 4%
0013463-67-7	TITANIUM DIOXIDE	3% - 4%
0000107-87-9	METHYL PROPYL KETONE	3% - 4%
0000106-42-3	P-XYLENE	2% - 3%
0000100-41-4	ETHYLBENZENE	2% - 3%
0000095-47-6	O-XYLENE	2% - 3%
0001330-20-7	XYLENE	0.09% - 2%
0008052-41-3	STODDARD SOLVENT	0.09% - 2%
0001328-53-6	POLYCHLOROCOPPER PHTHALOCYANINE	0.05% - 1%
0022464-99-9	ZIRCONIUM OCTOATE	0.03% - 0.63%
0001335-30-4	ALUMINUM SILICATE HYDRATE	0.03% - 0.61%
0007631-86-9	SILICA, AMORPHOUS	0.03% - 0.54%
0064742-89-8	ALIPHATIC, LIGHT HYDROCARBON SOLVENT	0.02% - 0.46%
0021645-51-2	ALUMINUM HYDROXIDE	0.02% - 0.36%
0068037-77-4	SILOXANES AND SILICONES, ET ME, ME 2-PHENYLPROPYL	0.02% - 0.30%
0064742-82-1	NAPHTHA (PETROLEUM) HYDRODESULFURIZED	0.01% - 0.25%
0000110-19-0	ISO-BUTYL ACETATE	0.01% - 0.25%
0000071-36-3	N-BUTYL ALCOHOL	0.01% - 0.25%
0000078-83-1	ISOBUTYL ALCOHOL	0.01% - 0.25%
0000096-29-7	2-BUTANONE OXIME	0.01% - 0.21%
0068412-53-3	(C9)BRANCHED ALKYLPHENOL, ETHOXYLATE, PHOSPHORATE	Trace
0000136-52-7	COBALT OCTATE	Trace

0000577-11-7	DI-2-ETHYLHEXYL SODIUM SULFOSUCCINATE	Trace
0064742-88-7	MEDIUM MINERAL SPIRITS	Trace
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	Trace
0001314-23-4	ZIRCONIA OXIDE	Trace
0091313-01-8	NON-HAZARDOUS, SOLID	Trace
0068412-54-4	POLY(OXY-1,2-ETHANEDIYL), ALPHA-(NONYLPHENYL)-OMEGA-HYDROXY-, BRANCHED	Trace
0064742-48-9	NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	Trace
0000136-51-6	CALCIUM 2-ETHYLHEXANOATE	Trace
0000122-99-6	ETHYLENE GLYCOL MONOPHENYL ETHER	Trace
0000095-63-6	1,2,4-TRIMETHYLBENZENE	Trace
0001309-37-1	FERRIC OXIDE	Trace
0064742-94-5	AROMATIC HYDROCARBON MIXTURE >C9	Trace
0012001-85-3	ZINC NAPHTHANATE	Trace
0000107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	Trace
0000111-46-6	DIETHYLENE GLYCOL	Trace
0000108-67-8	MESITYLENE	Trace
0000136-53-8	ZINC 2-ETHYLHEXANOATE	Trace
0000104-76-7	2-ETHYL-1-HEXANOL	Trace
0068954-84-7	POLY(OXY-1,2-ETHANEDIYL), .ALPHA.-(NONYLPHENYL)-.OMEGA.-HYDROXY-, BRANCHED, PHOSPHATES, SODIUM SALTS	Trace
0000098-83-9	(1-METHYL ETHENYL)-BENZENE	Trace
0000149-57-5	2-ETHYLHEXANOIC ACID	Trace
0014808-60-7	SILICA, CRYSTALLINE	Trace
0000556-67-2	OCTAMETHYLCYCLOTETRASIOLO	Trace
0000142-16-5	2-BUTENEDIOIC ACID (2Z)-, 1,4-BIS(2-ETHYLHEXYL) ESTER	Trace
0000079-09-4	PROPIONIC ACID	Trace
0000091-20-3	NAPHTHALENE	Trace
0000098-82-8	CUMENE	Trace
0007631-90-5	SODIUM BISULFITE	Trace
0025340-17-4	DIETHYLBENZENE	Trace

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor. Eliminate all ignition sources if safe to do so. Immediately call a POISON CENTER or doctor. For specific treatment see section 4. Take precautions to ensure your own safety (e.g. wear appropriate protective equipment).

Skin Contact

Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes or until medical aid is available. Store contaminated clothing under water and wash before re-use or discard. Remove source of exposure. For brief contact with a small amount: Rewarm with body heat. Get immediate medical advice/attention. For extensive contact or a large amount: Immediately call a POISON CENTER/doctor and follow their advice. For specific treatment see section 4. Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts).

Eye Contact

If eye irritation persists: Get medical advice/attention. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. Remove source of exposure. Immediately call a POISON CENTER/doctor and follow their advice. For specific treatment see section 4. Avoid direct contact. Wear chemical protective gloves, if necessary.

Ingestion

Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Immediately call a POISON CENTER or doctor.

Most important symptoms and effects, both acute and delayed

EYES: May cause moderate burning, tearing, redness and swelling.

SKIN: Moderate irritation and discomfort. Defatting of skin and redness.

INHALATION: Can cause irritation, coughing, shortness of breath. Irritation of the respiratory tract and the other.

INGESTION: Can cause nausea, vomiting and diarrhea.

mucous membranes. EYES: May cause moderate burning, tearing, redness and swelling.

SKIN: Moderate irritation and discomfort. Defatting of skin and redness.

INHALATION: Can cause irritation, coughing, shortness of breath. Irritation of the respiratory tract and the other.

INGESTION: Can cause nausea, vomiting and diarrhea.

mucous membranes. No data available. No data available.

Indication of any immediate medical attention and special treatment needed

Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire : Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards Arising from the Chemical

Fire will produce irritating gases. Runoff may pollute waterways Contents under pressure. May be ignited by friction, heat, sparks or flames. Containers can explode in a fire. Containers exposed to heat and flames may rupture with violent force. Cylinders exposed to fire may vent and release gas through pressure relief devices. Vapors will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to source of ignition and flash back.

Precautions for Firefighters

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Equipment

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Stay uphill and/or upstream. Ventilate closed spaces before entering. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Evacuate and isolate hazard area and keep unauthorized personnel away. Isolate area until aerosol has dispersed. Do not walk through released material. A vapor-suppressing foam may be used to reduce vapors.

Protective Equipment

See section 8 for specifics on protective personal equipment (PPE). Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Wear thermal protective clothing when handling refrigerated/cryogenic liquids.

Personal Precautions

Avoid breathing aerosol. Do not get on skin, eyes or clothing.

Environmental Precautions

Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Suppress aerosol with water spray jet. Avoid allowing water runoff to contact spilled material. Prevent spreading of vapors through sewers, ventilation systems and confined areas. Dike far ahead of liquid spill for later disposal.

Methods and Materials for Containment and Cleaning up

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal. Ventilate area after clean-up is complete. Rinse away with water. Dispose of contaminated materials according to federal, state and local regulations. Allow substance to evaporate.

SECTION 7) HANDLING AND STORAGE

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

Storage Room Requirements

Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and strong oxidizers. Store in approved containers and protect against physical damage. Take precautionary measures against electrostatic discharge. To avoid fire or explosion, dissipate static electricity during transfer by ground and bonding containers and equipment before transferring material. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

General

Wash hands after use. Avoid breathing vapor or mist. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. All containers must be properly labelled. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not get in eyes, on skin, or on clothing. Eyewash stations and showers should be available in areas where this material is used and stored

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

Skin Protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (mg/m3)
(1-METHYL-ETHENYL)-BENZENE		10			A3	URT irr; kidney dam; female repro dam	A3	480 ceiling
1,2,4-TRIMETHYLBENZENE		10			A4	CNS impair; hematologic eff		
2-ETHYL-1-HEXANOL		5			A3	URT & eye irr	A3	
2-ETHYLHEXANOIC ACID	5 (IFV)					Teratogenic eff		

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (mg/m3)
ACETONE		250		500	A4	URT & eye irr; CNS impair	A4; BEI	2400
ALIPHATIC, LIGHT HYDROCARBON SOLVENT	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];	(L)[N159](L)[N800]			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	2000
ALUMINUM HYDROXIDE	1 (R)				A4	Pneumoconiosis; LRT irr; neurotoxicity	A4	
ALUMINUM SILICATE HYDRATE	1 (R)				A4	Pneumoconiosis; LRT irr; neurotoxicity	A4	
AROMATIC HYDROCARBON MIXTURE >C9	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];	(L)[N159](L)[N800]			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	2000
BUTANE				1000 (EX)		CNS impair		
CUMENE		5			A3	URT adenoma; neurological eff	A3	245
ETHYL ACETATE		400				URT & eye irr		1400
ETHYLBENZENE		20			A3	URT & eye irr; ototoxicity; kidney eff; CNS impair	OTO;BEI	435
FERRIC OXIDE	5 (R)				A4	Pneumoconiosis	A4	[10]; [15]; [5];
ISO-BUTYL ACETATE		50		150		Eye & URT irr		700
ISOBUTYL ALCOHOL		50				Skin & eye irr		300
MEDIUM MINERAL SPIRITS	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];	(L)[N159](L)[N800]			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	
MESITYLENE		10				CNS impair; hematologic eff		
METHYL ETHYL KETONE		200		300		URT irr; CNS & PNS impair	BEI	590
METHYL PROPYL KETONE				150		Plum func; eye irr		700
M-XYLENE		20				Eye irr & URT irr, hemotologic effects; CNS impair		435
NAPHTHA (PETROLEUM) HYDRODESULFURIZED	[(L)]; [5 (I)];	(L)			[A2]; [A4];	URT irr	[A2]; [A4];	2000
NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];	(L)[N159](L)[N800]			[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr [N159]URT irr [N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	2000
NAPHTHALENE		10			A3	URT irr; cataracts; hemolytic anemia	Skin; A3; BEI	50
N-BUTYL ALCOHOL		20				Eye & URT irr		300

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (mg/m3)
O-XYLENE		20				Eye irr & URT irr, hemotologic effects; CNS impair		435
PROPANE				Simple asphyxiant (D), explosion hazard (EX)		Asphyxia		1800
PROPIONIC ACID		10				Eye, Skin, & URT irr		
PROPYLENE GLYCOL MONOMETHYL ETHER		50		100	A4	Eye & URT irr	A4	
P-XYLENE		20			A4	Eye irr & URT irr, hemotologic effects; ototoxicity; CNS impair		435
SILICA, AMORPHOUS								80 mg/m3 percent SiO2+2
SILICA, CRYSTALLINE	0.025 (R)				A2	Pulmonary fibrosis; lung cancer	A2	[10 mg/m3 percent SiO2+2 / 250 percent SiO2+5 mppcf]; [30 mg/m3 percent SiO2+2];
SODIUM BISULFITE	5				A4	Skin; eye, & URT irr	A4	
STODDARD SOLVENT	[(L)]; [5 (I)];	100			[A2]; [A4];	Eye, skin, & kidney dam; nausea; CNS impair	[A2]; [A4];	2900
TITANIUM DIOXIDE	0.2 (R)(Nano), 2.5 (R)				A3	LRT irr; pneumoconiosis		15
TOLUENE		20			A4	CNS, visual, & hearing impair; female repro system eff; pregnancy loss	OTO; A4; BEI	0.2
XYLENE		20				Eye irr & URT irr, hemotologic effects; CNS impair		435
ZIRCONIA OXIDE	5		10		A4	Resp irr	A4	5
ZIRCONIUM OCTOATE	5		10		A4	Resp irr	A4	5

Chemical Name	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Tables (Z1, Z2, Z3)	OSHA Skin designation	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
(1-METHYL ETHENYL)- BENZENE	100 ceiling				1		240	50
1,2,4- TRIMETHYLBENZENE							125	25
2-ETHYL-1- HEXANOL								
2- ETHYLHEXANOIC ACID								
ACETONE	1000				1		590	250

Chemical Name	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Tables (Z1, Z2, Z3)	OSHA Skin designation	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
ALIPHATIC, LIGHT HYDROCARBON SOLVENT	500				1			
ALUMINUM HYDROXIDE								
ALUMINUM SILICATE HYDRATE								
AROMATIC HYDROCARBON MIXTURE >C9	500				1			
BUTANE							1900	800
CUMENE	50				1	1	245	50
ETHYL ACETATE	400				1		1400	400
ETHYLBENZENE	100				1		435	100
FERRIC OXIDE					1			
ISO-BUTYL ACETATE	150				1		700	150
ISOBUTYL ALCOHOL	100				1		150	50
MEDIUM MINERAL SPIRITS								
MESITYLENE							125	25
METHYL ETHYL KETONE	200				1		590	200
METHYL PROPYL KETONE	200				1		530	150
M-XYLENE	100				1		435	100
NAPHTHA (PETROLEUM) HYDRODESULFURIZED	500				1			
NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	500				1			
NAPHTHALENE	10				1		50	10
N-BUTYL ALCOHOL	100				1			
O-XYLENE	100				1		435	100
PROPANE	1000				1		1800	1000
PROPIONIC ACID							30	10
PROPYLENE GLYCOL MONOMETHYL ETHER							360	100
P-XYLENE	100				1		435	100

Chemical Name	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Tables (Z1, Z2, Z3)	OSHA Skin designation	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
SILICA, AMORPHOUS	20 (b)				1,3		6	
SILICA, CRYSTALLINE	a				[1,3]; [3];		0.05e	
SODIUM BISULFITE							5	
STODDARD SOLVENT	500				1		350	
TITANIUM DIOXIDE					1			b
TOLUENE	200 (a)/ 300 ceiling		500ppm /10 minutes (a)		1,2		375	100
XYLENE	100				1		435	100
ZIRCONIA OXIDE					1			
ZIRCONIUM OCTOATE					1			

Chemical Name	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
(1-METHYL ETHENYL)- BENZENE	485	100	
1,2,4- TRIMETHYLBE NZENE			
2-ETHYL-1- HEXANOL			
2- ETHYLHEXAN OIC ACID			
ACETONE			
ALIPHATIC, LIGHT HYDROCARBO N SOLVENT			
ALUMINUM HYDROXIDE			
ALUMINUM SILICATE HYDRATE			
AROMATIC HYDROCARBO N MIXTURE >C9			
BUTANE			
CUMENE			
ETHYL ACETATE			
ETHYLBENZE NE	545	125	
FERRIC OXIDE			
ISO-BUTYL ACETATE			
ISOBUTYL ALCOHOL			
MEDIUM MINERAL SPIRITS			

Chemical Name	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
MESITYLENE			
METHYL ETHYL KETONE	885	300	
METHYL PROPYL KETONE			
M-XYLENE	655	150	
NAPHTHA (PETROLEUM) HYDRODESULFURIZED			
NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)			
NAPHTHALENE	75	15	
N-BUTYL ALCOHOL			
O-XYLENE	655	150	
PROPANE			
PROPIONIC ACID	45	15	
PROPYLENE GLYCOL MONOMETHYL ETHER	540	150	
P-XYLENE	655	150	
SILICA, AMORPHOUS			
SILICA, CRYSTALLINE			1
SODIUM BISULFITE			
STODDARD SOLVENT			
TITANIUM DIOXIDE			1
TOLUENE	560	150	
XYLENE	655	150	
ZIRCONIA OXIDE			
ZIRCONIUM OCTOATE			

(L) - Exposure by all routes should be carefully controlled to levels as low as possible, LRT - Lower respiratory tract, CNS - Central nervous system, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, repro - reproductive, A4 - Not Classifiable as a Human Carcinogen, dam - Damage, func - Function, PNS - Peripheral nervous system, URT - Upper respiratory tract, (IFV) - Inhalable fraction and vapor, A2 - Suspected Human Carcinogen, irr - Irritation, BEI - Substances for which there is a Biological Exposure Index or Indices, eff - Effects, (R) - Respirable fraction, resp - respiratory, impair - Impairment

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Density	7.32790 lb/gal
Specific Gravity	0.87808
% VOC	46.41690%
% Solids By Weight	29.47860%
Density VOC	3.40138 lb/gal
% HAPS	23.41530%
Density HAPS	1.71585 lb/gal
% VHAPS	23.33020%
Density VHAPS	1.70961 lb/gal

Appearance	N/A
Odor Threshold	N/A
Odor Description	N/A
Water Solubility	N/A
Flammability	N/A
Flash Point Symbol	N/A
pH	N/A
Flash Point	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Density	N/A
Vapor Pressure	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Melting Point	N/A
Freezing Point	N/A
Kinematic Viscosity	N/A
Kinematic Viscosity Temperature	N/A
Auto Ignition Temp	N/A
Evaporation Rate	N/A
Decomposition Pt	N/A
Coefficient Water/Oil	N/A

SECTION 10) STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical Stability

Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions/Polymerization

Will not occur.

Conditions To Avoid

Avoid heat, sparks, flame, high temperature, freezing and contact with incompatible materials. Avoid all possible sources of ignition.

Incompatible Materials

Strong bases, acids, and oxidizing agents.

Hazardous Decomposition Products

Oxides of carbon.

Skin Corrosion/Irritation

Contact with skin can cause moderate irritation and discomfort. Defatting of skin and redness are possible.

Causes skin irritation

0000067-64-1 ACETONE

Can cause skin irritation.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate and burn the skin.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the skin.

0000108-88-3 TOLUENE

Contact can irritate the skin.

0000111-46-6 DIETHYLENE GLYCOL

May cause mild skin irritation.

0000141-78-6 ETHYL ACETATE

Exposure to high levels can cause dizziness and lightheadedness.

Serious Eye Damage/Irritation

May cause moderate burning, tearing, redness and swelling.

Causes serious eye irritation

0000067-64-1 ACETONE

Exposure can irritate the eyes.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate and burn the eyes.

0000078-83-1 ISOBUTYL ALCOHOL

Contact with eyes is extremely irritating and may cause burns.

0000078-93-3 METHYL ETHYL KETONE

Contact can severely irritate and burn the eyes.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the eyes.

0000108-88-3 TOLUENE

Contact can irritate the eyes.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Vapor is a mild eye irritant.

Respiratory/Skin Sensitization

Inhalation may cause: irritation, coughing, shortness of breath. Irritation of the respiratory tract and the other mucous membranes.

May cause an allergic skin reaction

0000067-64-1 ACETONE

Can irritate the nose and throat causing coughing and wheezing.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate the nose, throat and lungs. May cause dryness or cracking.

0000078-83-1 ISOBUTYL ALCOHOL

Can irritate the skin causing a rash. Breathing can irritate the nose, mouth and throat causing coughing and wheezing.

0000078-93-3 METHYL ETHYL KETONE

Can irritate the skin causing a rash. Breathing can irritate the nose and throat causing coughing and wheezing.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance and the vapour in high concentrations can be irritating to the respiratory tract.

0000108-88-3 TOLUENE

Inhaling can irritate the nose and throat.

0000110-19-0 ISO-BUTYL ACETATE

The substance defats the skin, which may cause dryness or cracking.

Germ Cell Mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer

Reproductive Toxicity

Suspected of damaging fertility or the unborn child

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The NOAEL for paternal toxicity is 300 ppm and for offspring toxicity is 1000 ppm. The NOAEL for maternal and fetotoxicity was considered to be 1500 ppm. Effects appear secondary to parental weight loss.

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness

0000067-64-1 ACETONE

May affect the kidneys and liver.

0000071-36-3 N-BUTYL ALCOHOL

Exposure can cause headache, dizziness, nausea and vomiting. Can damage the liver and kidneys.

0000078-83-1 ISOBUTYL ALCOHOL

Exposure can cause headache, dizziness, drowsiness, confusion and loss of coordination. It may affect the liver.

0000078-93-3 METHYL ETHYL KETONE

Exposure can cause dizziness, lightheadedness, headache, nausea, and blurred vision.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Exposure to very high concentrations could cause depression of the central nervous system.

0000108-88-3 TOLUENE

May affect the nervous system causing headache, dizziness and passing out.

0000111-46-6 DIETHYLENE GLYCOL

Ingestion may cause effects on the central nervous system, the liver, and the kidneys (including kidney impairment).

0000141-78-6 ETHYL ACETATE

Can affect the liver and kidneys.

Specific Target Organ Toxicity - Repeated Exposure

Causes damage to organs through prolonged or repeated exposure.

0000078-93-3 METHYL ETHYL KETONE

Repeated high exposure can damage the nervous system and may affect the brain.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance defats the skin, which may cause dryness or cracking. Prolonged exposure to vapors may cause coughing, shortness of breath, dizziness and intoxication.

0000108-88-3 TOLUENE

Repeated exposure may cause liver, kidney and brain damage.

0000110-19-0 ISO-BUTYL ACETATE

The vapour is mildly irritating to the eyes and respiratory tract. The substance may cause effects on the central nervous system. Exposure far above the OEL could cause lowering of consciousness.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

Chronic Exposure

0000098-82-8 CUMENE

TERATOGENIC EFFECTS: Cumene has been Classified as POSSIBLE for humans.

0000100-41-4 ETHYLBENZENE

CARCINOGENIC EFFECTS: Ethyl Benzene has been listed by IARC as Group 2B, Possibly Carcinogenic to Humans.

TERATOGENIC EFFECTS: Ethyl Benzene has been Classified as POSSIBLE for humans.

0000108-88-3 TOLUENE

TERATOGENIC EFFECTS: Toluene has been Classified as POSSIBLE for humans.

0001330-20-7 XYLENE

High exposure to Xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus.

Xylene in high concentrations has caused embryotoxic effects in laboratory animals.

0014808-60-7 SILICA, CRYSTALLINE

Prolonged inhalation of respirable crystalline silica dust can result in lung disease (i.e. silicosis and/or lung cancer). Symptoms include coughing, shortness of breath, wheezing and reduced pulmonary function.

Aspiration Hazard

May be fatal if swallowed and enters airways

0000078-83-1 ISOBUTYL ALCOHOL

If swallowed, aspiration into the lungs may result in chemical pneumonitis.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

If liquid is swallowed, it may get into lungs by aspiration

Potential Health Effects - Miscellaneous

0000108-88-3 TOLUENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. Can be absorbed through the skin in harmful amounts. Recurrent overexposure may result in liver and kidney injury. High airborne levels have produced irregular heart beats in animals and occasional palpitations in humans. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. WARNING: This chemical is known to the State of California to cause birth defects or other reproductive harm.

0000141-78-6 ETHYL ACETATE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: blood, kidneys, liver.

0001330-20-7 XYLENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

0000071-36-3 N-BUTYL ALCOHOL

May cause abnormal blood forming function with anemia. Liquid splashes in the eye may result in chemical burns.

0000078-83-1 ISOBUTYL ALCOHOL

Has shown carcinogenic activity in laboratory animals at high doses. Significance to man is unknown. May cause irritation of the mucous membranes. May cause abnormal liver function. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: bone marrow, liver. Prolonged skin contact may cause chemical burns. Liquid splashes in the eye may result in chemical burns.

0000078-93-3 METHYL ETHYL KETONE

Material is irritating to mucous membranes and upper respiratory tract. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, eyes, respiratory system, skin. Prolonged or repeated overexposure may cause any of the following: conjunctivitis, dermatitis. High concentrations have caused embryotoxic effects in laboratory animals. Aspiration may occur during swallowing or vomiting, resulting in lung damage. Ingestion may cause headache, nausea, vomiting, dizziness, and drowsiness.

0000091-20-3 NAPHTHALENE

Is an IARC, NTP or OSHA carcinogen. Tests in some laboratory animals demonstrate carcinogenic activity. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: kidneys, liver. Recurrent overexposure may result in liver and kidney injury. WARNING: This chemical is known to the State of California to cause cancer.

0000100-41-4 ETHYLBENZENE

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

0000107-87-9 METHYL PROPYL KETONE

May cause temporary upper respiratory and/or lung irritation with cough, difficult breathing, or shortness of breath. May cause any of the following central nervous system effects: drowsiness. May cause eye irritation with discomfort, tearing, or blurred vision.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Tests in laboratory animals have shown effects on any of the following organs/systems: kidneys, liver. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

0013463-67-7 TITANIUM DIOXIDE

Is an IARC, NTP or OSHA carcinogen. In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m³ respirable titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was overwhelmed and that the results at the massive 250 mg/m³ level are not relevant to the workplace. Results of a DuPont epidemiology study showed that employees who had been exposed to Titanium Dioxide were at no greater risk of developing lung cancer than were employees who had not been exposed to Titanium dioxide. No pulmonary fibrosis was found in any of the employees and no association was observed between Titanium dioxide exposure and chronic respiratory disease or x-ray abnormalities. Based on the results of this study DuPont concludes that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.

0014808-60-7 SILICA, CRYSTALLINE

Is an IARC, NTP or OSHA carcinogen. Repeated overexposure to crystalline silica may lead to x-ray changes and chronic lung disease. Inhalation of high dust concentrations may cause: breathing difficulties, lung injury. WARNING: This chemical is known to the State of California to cause cancer.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-88-7 MEDIUM MINERAL SPIRITS

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. This substance may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, lungs, reproductive system, skin. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-89-8 ALIPHATIC, LIGHT HYDROCARBON SOLVENT

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

0064742-95-6 AROMATIC HYDROCARBON MIXTURE >C9

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

Acute Toxicity

Ingestion may cause nausea, vomiting and diarrhea.

May be harmful if swallowed

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is 3097.14 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

0000078-83-1 ISOBUTYL ALCOHOL

If swallowed, aspiration into the lungs may result in chemical pneumonitis.

0000111-46-6 DIETHYLENE GLYCOL

Ingestion can lead to death.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Inhalation of high concentrations can cause CNS depression; Ingestion can cause aspiration into the lungs.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

High concentration of vapors may cause intoxication

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

0000067-64-1 ACETONE

Substance can be absorbed into the body by inhalation.

0000071-36-3 N-BUTYL ALCOHOL

Can be absorbed into the body by inhalation of its vapour and by ingestion.

0000078-83-1 ISOBUTYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

0000078-93-3 METHYL ETHYL KETONE

Can be absorbed into the body by inhalation, by ingestion and through the skin.

0000106-97-8 BUTANE

The substance can be absorbed into the body by inhalation.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance can be absorbed into the body by inhalation of its aerosol or vapour, through the skin and by ingestion.

0000108-88-3 TOLUENE

The substance can be absorbed into the body by inhalation, through the skin and by ingestion.

0000110-19-0 ISO-BUTYL ACETATE

The substance can be absorbed into the body by inhalation of its vapour.

0000111-46-6 DIETHYLENE GLYCOL

Ingestion.

0000067-64-1 ACETONE

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m³ (4-hour exposure) (29)

LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m³ (4-hour exposure) (29)

LD50 (oral, female rat): 5800 mg/kg (24)

LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31)

LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)

LD50 (oral, mouse): 3000 mg/kg (32,unconfirmed)

LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg) (30)

0000071-36-3 N-BUTYL ALCOHOL

LC50 (rat): greater than 8000 ppm (4-hour exposure) (14)

LD50 (oral, rat): 2510 mg/kg (15)

LD50 (oral, male rat): 790 mg/kg (16)*

LD50 (oral, female rat): 2020 mg/kg (16)* *(Note: the rats used in this study appear to have been very young (60-100 grams).)

LD50 (oral, hamster): 1200 mg/kg (11, original

0000078-83-1 ISOBUTYL ALCOHOL

LD50 (oral, rat): 2460 mg/kg.(7)

LD50 (oral, rabbit): 3000 mg/kg (reported as 41 mmol/kg) (8)

LD50 (dermal, rabbit): 3400 mg/kg (reported as 4.24 mL/kg).(7)

0000078-93-3 METHYL ETHYL KETONE

LC50 (male rat): 11,700 ppm (4-hour exposure) (3)

LC50 (male rat): 11,300 ppm (4-hour exposure); cited as 23.5 mg/L (7,990 ppm) (8-hour exposure) (4)

LD50 (oral, adult male rat): 2,740 mg/kg; cited as 3.4 mL/kg (1)

LD50 (dermal, rabbit): greater than 5,000 mg/kg (29)

0000079-09-4 PROPIONIC ACID

LD50 (oral, rat): 4270 mg/kg (6)

LD50 (oral, rat): 2600 mg/kg (7, unconfirmed)

LD50 (dermal, rabbit): 500 mg/kg (6)

0000091-20-3 NAPHTHALENE

LC50: Insufficient data

LD50 (oral, mouse): 533 mg/kg (male); 710 mg/kg (female) (1)

LD50 (oral, rat): 1780 mg/kg (2)

0000095-47-6 O-XYLENE

LC50 (rat): 5300 ppm (4-hour exposure); cited as 4330 ppm (6-hour exposure) (3)

LC50 (mouse): 5630 ppm (4-hour exposure); cited as 4595 ppm (6-hour exposure) (3,4)

LD50 (oral, rat): 3608 mg/kg (3,16)

LD50 (dermal, rabbit): 20000 mg/kg (3)

0000095-63-6 1,2,4-TRIMETHYLBENZENE

LC50 (rat): 18 g/m3 (4-hour exposure) (1)

LD50 (oral, rat): 5 g/kg (1)

0000098-82-8 CUMENE

LC50 (inhalation, mouse): 10 mg/L; (2000 ppm); 7-hr exposure (1,3)

LC50 (inhalation, rat): 39 mg/L (8000 ppm); 4-hr exposure (1,3,6)

LD50 (oral, rat): Reported as 1.4 g/kg and 2.26 g/kg (1,3,4)

LD50 (skin, rabbit): 10627 mg/kg (4)

0000100-41-4 ETHYLBENZENE

LC50 (inhalation, rat): 4000 ppm; 4-hour exposure (3)

LD50 (oral, rat): 3.5 g/kg (1,3,5,10)

LD50 (oral, rat): 4.72 g/kg (3,5,7,8)

LD50 (dermal, rabbit): 17.8 g/kg (11)

0000106-42-3 P-XYLENE

LC50 (rat): 4740 ppm (4-hour exposure) (3)

LC50 (mouse): 4800 ppm (4-hour exposure); cited as 3900 ppm (6-hour exposure) (1,4,6)

LD50 (oral, rat): 4030 mg/kg (3); 4550 mg/kg (10)

0000107-87-9 METHYL PROPYL KETONE

LD50 (oral, rat): 3017 mg/kg (cited as 3.73 mL/kg) (10)

LD50 (dermal, rabbit): 6472 mg/kg (cited as 8.00 mL/kg) (10)

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

LC50 (rat): 15000 ppm; 4-hr exposure (2)

LC50 (guinea pig): 15000 ppm; 10-hr exposure (2)

LD50 (oral, rat): 6.6 g/kg (5.2-7.5 g/kg) (10)

LD50 (oral, mouse): 10.7-10.8 g/kg (2,12)

LD50 (oral, dog): 4.6-5.5 g/kg (2); approximately 9.2 g/kg (2)

LD50 (oral, rabbit): 5.2-5.3 g/kg (2,12)

LD50 (dermal, rabbit): 13-14 g/kg (10)

0000108-38-3 M-XYLENE

LC50 (rat): 7330 ppm (4-hour exposure); cited as 5984 ppm (6-hour exposure) (3,17)

LC50 (mouse): 6450 ppm (4-hour exposure); cited as 5267 ppm (6-hour exposure) (3)

LD50 (oral, rat): 5011 mg/kg (3); 6660 mg/kg (3)

LD50 (dermal, rabbit): 12180 mg/kg (3,17)

0000108-67-8 MESITYLENE

LC50 (rat): 24 g/m3 (4-hour exposure) (2)

0000108-88-3 TOLUENE

LC50 (rat): 8800 ppm (4-hour exposure) (2)

LC50 (rat): 6000 ppm (6-hour exposure) (3)

LD50 (oral, rat): 2600 to 7500 mg/kg (3,5,11,17)

LD50 (oral, neonatal rat): less than 870 mg/kg (3)

LD50 (dermal, rabbit): 12,225 mg/kg (reported as 14.1 mL/kg) (1)

0000110-19-0 ISO-BUTYL ACETATE

LC50 (rat): approximately 8000 ppm (4-hour exposure); 4 out of 6 rats died (3)

LD50 (oral, rat): 13400 mg/kg (cited as 15.4 mL/kg) (1)

LD50 (oral, rabbit): 4800 mg/kg (cited as 41 mmol/kg) (4)

LD50 (dermal, rabbit): Greater than 5000 mg/kg (1)

0000141-78-6 ETHYL ACETATE

LC50 (rat): 19600 ppm (4-hour exposure); cited as 16000 ppm (6-hour exposure) (10)

LC50 (mouse): 10600 ppm (38100 mg/m3) (4-hour exposure); cited as 44000 mg/m3 (3-hour exposure) (8)
LD50 (oral, rat): 10200 mg/kg (cited as 11.3 mL/kg) (7); 5600 mg/kg (5,13)
LD50 (oral, mouse): 4100 mg/kg (11)
LD50 (oral, rabbit): 4900 mg/kg (9)
LD50 (oral, guinea pig): 5500 mg/kg (11)
LD50 (dermal, rabbit): Greater than 18000 mg/kg (cited as 20 mL/kg) (7)

0001330-20-7 XYLENE

LC50 (rat): 6350 ppm (4-hour exposure) (unspecified isomers and ethylbenzene) (1)LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene) (2) ethylbenzene) (1)
LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene)(2)
LD50 (oral, rat): 5400 mg/kg (52% m-, 19% o-, 24% p-) (1)LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)
LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)
LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

0008052-41-3 STODDARD SOLVENT

LC50 (rat): greater than 5500 mg/m3 (880 ppm) (whole body exposure for 4 hours) (1)
LC50 (rat): greater than 8200 mg/m3 (1300 ppm) (2)
LD50 (oral, rat): greater than 5 g/kg (1)
LD50 (dermal, rabbit): greater than 3 g/kg (1)

0013463-67-7 TITANIUM DIOXIDE

LC50 (inhalation, Rat): >5.09 mg/L ; 4-hr exposure
Test atmosphere: dust/mist
No mortality observed at this dose.
LD50 Rat: > 5000 mg/kg

LD50 Hamster: > 10000 mg/kg

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

LC50 (Rodent - rat, Inhalation) : >590 mg/m3 (4 hour exposure) Toxic effects : Details of toxic effects not reported other than lethal dose value.
LD50 (Rodent - rabbit, Administration onto the skin) : >2 mL/kg ,Toxic effects : Behavioral - somnolence (general depressed activity) Behavioral - changes in motor activity (specific assay) Behavioral - irritability

0000106-97-8 BUTANE

LC50 (mouse): 202000 ppm (481000 mg/m3) (4-hour exposure); cited as 680 mg/L (2-hour exposure) (9)
LC50 (rat): 276000 ppm (658000 mg/m3) (4-hour exposure); cited as 658 mg/L (4-hour exposure) (9)

SECTION 12) ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life

Harmful to aquatic life with long lasting effects

Persistence and Degradability

0000067-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

Readily biodegradable.

0000071-36-3 N-BUTYL ALCOHOL

Readily biodegradable.

0000078-93-3 METHYL ETHYL KETONE

Readily biodegradable.

0000106-97-8 BUTANE

Readily biodegradable.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

Readily biodegradable in water. Half-life in air = 3.1 hours.

0000110-19-0 ISO-BUTYL ACETATE

Readily biodegradable.

0000111-46-6 DIETHYLENE GLYCOL

Readily biodegradable.

0001330-20-7 XYLENE

50% of applied radiolabelled o-xylene was mineralised in 23 days, and 50% p-xylene was mineralised in 13 days.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Readily biodegradable

Bioaccumulative Potential

0000110-19-0 ISO-BUTYL ACETATE

No potential for bioaccumulation.

0000111-46-6 DIETHYLENE GLYCOL

Bioaccumulation is not expected.

0064742-94-5 AROMATIC HYDROCARBON MIXTURE >C9

Has the potential to bioaccumulate.

Mobility in Soil

0000067-64-1 ACETONE

The substance is not PBT / vPvB.

0000078-93-3 METHYL ETHYL KETONE

The substance is not PBT / vPvB.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000071-36-3 N-BUTYL ALCOHOL

The substance is not PBT / vPvB.

0000106-97-8 BUTANE

Readily biodegradable.

The substance is not PBT / vPvB.

0000107-98-2 PROPYLENE GLYCOL MONOMETHYL ETHER

The substance is not PBT / vPvB.

0000111-46-6 DIETHYLENE GLYCOL

The substance is not PBT / vPvB.

0000141-78-6 ETHYL ACETATE

The substance is not PBT / vPvB.

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION

	U.S. DOT Information	IMDG Information	IATA Information
UN number:	UN1950	UN1950	UN1950
Proper shipping name:	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Hazard class:	2.1	2.1	2.1
Packaging group:	NA	NA	NA
Hazardous substance (RQ):	No Data Available		
Marine Pollutant:	No Data Available	No Data Available	
Note / Special Provision:	No Data Available	No Data Available	No Data Available
Toxic-Inhalation Hazard:	No Data Available		

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0000067-64-1	ACETONE	22% - 27%	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),
proprietary	ALKYD RESIN	16% - 22%	SARA312,
0000108-88-3	TOLUENE	8% - 10%	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, TSCA - Toxic Substances Control Act (TSCA), CA_Prop65 - California Proposition 65,
0000108-38-3	M-XYLENE	5% - 7%	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000074-98-6	PROPANE	4% - 6%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000106-97-8	BUTANE	4% - 6%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
NA-Repcolite	ALKYD RESIN	4% - 5%	SARA312,
0000078-93-3	METHYL ETHYL KETONE	3% - 4%	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000141-78-6	ETHYL ACETATE	3% - 4%	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0013463-67-7	TITANIUM DIOXIDE	3% - 4%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA), CA_Prop65 - California Proposition 65,
0000107-87-9	METHYL PROPYL KETONE	3% - 4%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000106-42-3	P-XYLENE	2% - 3%	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000100-41-4	ETHYLBENZENE	2% - 3%	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, TSCA - Toxic Substances Control Act (TSCA), CA_Prop65 - California Proposition 65,
0000095-47-6	O-XYLENE	2% - 3%	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0001330-20-7	XYLENE	0.09% - 2%	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0008052-41-3	STODDARD SOLVENT	0.09% - 2%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),

0001328-53-6	POLYCHLOROCOPPER PHTHALOCYANINE	0.05% - 1%	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0022464-99-9	ZIRCONIUM OCTOATE	0.03% - 0.63%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0001335-30-4	ALUMINUM SILICATE HYDRATE	0.03% - 0.61%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0007631-86-9	SILICA, AMORPHOUS	0.03% - 0.54%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0064742-89-8	ALIPHATIC, LIGHT HYDROCARBON SOLVENT	0.02% - 0.46%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0021645-51-2	ALUMINUM HYDROXIDE	0.02% - 0.36%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0068037-77-4	SILOXANES AND SILICONES, ET ME, ME 2-PHENYLPROPYL	0.02% - 0.30%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0064742-82-1	NAPHTHA (PETROLEUM) HYDRODESULFURIZED	0.01% - 0.25%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000110-19-0	ISO-BUTYL ACETATE	0.01% - 0.25%	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000071-36-3	N-BUTYL ALCOHOL	0.01% - 0.25%	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000078-83-1	ISOBUTYL ALCOHOL	0.01% - 0.25%	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000096-29-7	2-BUTANONE OXIME	0.01% - 0.21%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0068412-53-3	(C9)BRANCHED ALKYLPHENOL, ETHOXYLATE, PHOSPHORATE	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000136-52-7	COBALT OCTATE	Trace	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000577-11-7	DI-2-ETHYLHEXYL SODIUM SULFOSUCCINATE	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0064742-88-7	MEDIUM MINERAL SPIRITS	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0001314-23-4	ZIRCONIA OXIDE	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0091313-01-8	NON-HAZARDOUS, SOLID	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0068412-54-4	POLY(OXY-1,2-ETHANEDIYL), ALPHA-(NONYLPHENYL)- OMEGA-HYDROXY-, BRANCHED	Trace	SARA313, DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0064742-48-9	NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000136-51-6	CALCIUM 2-ETHYLHEXANOATE	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000122-99-6	ETHYLENE GLYCOL MONOPHENYL ETHER	Trace	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000095-63-6	1,2,4-TRIMETHYLBENZENE	Trace	SARA313, DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0001309-37-1	FERRIC OXIDE	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0064742-94-5	AROMATIC HYDROCARBON MIXTURE >C9	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0012001-85-3	ZINC NAPHTHANATE	Trace	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),

0000107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000111-46-6	DIETHYLENE GLYCOL	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000108-67-8	MESITYLENE	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000136-53-8	ZINC 2-ETHYLHEXANOATE	Trace	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000104-76-7	2-ETHYL-1-HEXANOL	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0068954-84-7	POLY(OXY-1,2-ETHANEDIYL), .ALPHA.- (NONYLPHENYL)-.OMEGA.- HYDROXY-, BRANCHED, PHOSPHATES, SODIUM SALTS	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000098-83-9	(1-METHYL ETHENYL)- BENZENE	Trace	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA), CA_Prop65 - California Proposition 65,
0000149-57-5	2-ETHYLHEXANOIC ACID	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0014808-60-7	SILICA, CRYSTALLINE	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA), CA_Prop65 - California Proposition 65,
0000556-67-2	OCTAMETHYLCYCLOTETRASIL O	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000142-16-5	2-BUTENEDIOIC ACID (2Z)-, 1,4-BIS(2-ETHYLHEXYL) ESTER	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000079-09-4	PROPIONIC ACID	Trace	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0000091-20-3	NAPHTHALENE	Trace	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, TSCA - Toxic Substances Control Act (TSCA), CA_Prop65 - California Proposition 65,
0000098-82-8	CUMENE	Trace	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, TSCA - Toxic Substances Control Act (TSCA), CA_Prop65 - California Proposition 65,
0007631-90-5	SODIUM BISULFITE	Trace	DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA),
0025340-17-4	DIETHYLBENZENE	Trace	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA),

The information in this Section does not list non-hazardous components that might have relevant , SARA312 regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.

Product does not contain any chemicals listed under California Proposition 65

SECTION 16) OTHER INFORMATION


Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

HMIS

Health	/ 2
FLAMMABILITY	4
Physical Hazard	0
Personal Protection	X

NFPA



(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.