

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Xylene
Product Use Description : Solvent.

Manufacturer or supplier's details

Company : Nexeo Solutions LLC
Address : 3 Waterway Square Place Suite 1000
 Woodlands, Tx. 77380
 United States of America

Emergency telephone number:

Health North America: 1-855-NEXEO4U (1-855-639-3648)
 Health International: 1-855-NEXEO4U (1-855-639-3648)
 Transport North America: CHEMTREC 800.424.9300

Additional Information: : Responsible Party: Product Safety Group
 E-Mail: msds@nexeosolutions.com
 SDS Requests: 1-855-429-2661
 SDS Requests Fax: 1-281-500-2370
 Website: www.nexeosolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure : Category 2 (Liver, Kidney, Central nervous system)

Specific target organ toxicity - repeated exposure (Oral) : Category 2

Aspiration hazard : Category 1

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

GHS Label element

Hazard pictograms



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 + H332 Harmful in contact with skin or if inhaled
H335 May cause respiratory irritation.
H315+H318 Causes skin and serious eye irritation
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical Name	Concentration (%)
1330-20-7	Mixed xylenes	90 - 100
100-41-4	**Ethylbenzene	0 - 30
108-88-3	**Toluene	1 - 5
98-82-8	**Cumene	0.1 - 1

Special Notes: : Mixed Xylenes contains the isomers o-, m-, p- Xylene, and Ethylbenzene. Trace amounts of Toluene and Benzene may also be present as impurities., ** Other substances in the product which may present a health or environmental hazard.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|--|
| Suitable extinguishing media | : Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : No hazardous combustion products are known |
| Specific extinguishing methods | : Use a water spray to cool fully closed containers. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for fire-fighting if necessary. |

NFPA Flammable and Combustible Liquids Classification:

Flammable Liquid Class IC

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions | : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and | : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, |

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

cleaning up

diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1330-20-7	Mixed xylenes	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	100 ppm 435 mg/m ³	OSHA Z-1
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m ³	NIOSH REL

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

		ST	125 ppm 545 mg/m ³	NIOSH REL
		TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	100 ppm 435 mg/m ³	OSHA P0
		STEL	125 ppm 545 mg/m ³	OSHA P0
108-88-3	**Toluene	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m ³	NIOSH REL
		ST	150 ppm 560 mg/m ³	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m ³	OSHA P0
		STEL	150 ppm 560 mg/m ³	OSHA P0
98-82-8	**Cumene	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m ³	NIOSH REL
		TWA	50 ppm 245 mg/m ³	OSHA Z-1
		TWA	50 ppm 245 mg/m ³	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
**Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift at end of work-week	0.7 g/g creatinine	ACGIH BEI
**Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after	0.03 mg/l	ACGIH BEI

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

				expo- sure ceases)		
		o-Cresol	Urine	End of shift (As soon as possible after expo- sure ceases)	0.3 mg/g Creatinine	ACGIH BEI

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : clear, colourless
Odour : sweet, aromatic, hydrocarbon-like
Odour Threshold : No data available

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

pH	: No data available
Freezing Point (Melting point/freezing point)	: -48 - -25 °C (-54 - -13 °F)
Boiling Point (Boiling point/boiling range)	: 138 - 142 °C (280 - 288 °F)
Flash point	: 27 °C (81 °F)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Burning rate	: No data available
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 1 %(V)
Vapour pressure	: 7 mmHg @ 20 °C (68 °F)
Relative vapour density	: 3.7(Air = 1.0)
Relative density	: 0.87Reference substance: (water = 1)
Density	: 0.8632 g/cm ³
Bulk density	: No data available
Solubility(ies)	
Water solubility	: practically insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 432 °C
Thermal decomposition	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

	normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No hazards to be specially mentioned.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: Acids alkalis Strong oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

1330-20-7:

Acute oral toxicity	: LD50 (rat, male): 3,523 mg/kg Method: EU Method B.1 (Acute Toxicity, Oral) GLP: no
Acute inhalation toxicity	: LC50 (rat, male): 6700 ppm Exposure time: 4 h Method: Directive 67/548/EEC, Annex V, B.2. Assessment: The component/mixture is moderately toxic after short term inhalation.
Acute dermal toxicity	: LD50 (rabbit): 1,100 mg/kg Assessment: The component/mixture is moderately toxic after single contact with skin.

Skin corrosion/irritation

Product:

Result: Irritating to skin.

Components:

1330-20-7:

Species: rabbit
Exposure time: 24 h
Result: Irritating to skin.

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

Serious eye damage/eye irritation

Product:

Result: Irritating to eyes.

Components:

1330-20-7:

Species: rabbit

Result: Irritating to eyes.

Respiratory or skin sensitisation

Components:

1330-20-7:

Remarks: No data available

Germ cell mutagenicity

Components:

1330-20-7:

- | | |
|-----------------------------------|--|
| Genotoxicity in vitro | : Test Type: Chromosome aberration test in vitro
Test species: Chinese hamster ovary (CHO)
Metabolic activation: with and without metabolic activation
Method: Mutagenicity (in vitro mammalian cytogenetic test)
Result: negative |
| | : Test Type: Sister chromatid exchange assay in mammalian cells
Test species: Chinese hamster ovary (CHO)
Metabolic activation: with and without metabolic activation
Result: negative |
| Genotoxicity in vivo | : Test Type: Dominant lethal assay
Test species: mouse
Application Route: Subcutaneous
Exposure time: 8 wk
Dose: 1.0 mL/kg
Method: OECD Test Guideline 478
Result: negative
GLP: no |
| Germ cell mutagenicity-Assessment | : Animal testing did not show any mutagenic effects. |

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

Carcinogenicity

Components:

1330-20-7:

Species: mouse, (male and female)
Application Route: Oral
Exposure time: 103 wk
Dose: 0, 500 or 1000 mg/kg
Frequency of Treatment: 5 days/week
Method: Directive 67/548/EEC, Annex V, B.32.
Result: did not display carcinogenic properties
GLP: No data available

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.

100-41-4:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

98-82-8:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Components:

1330-20-7:

Effects on fertility : Test Type: Two-generation study
Species: rat, male and female
Application Route: Inhalation
Dose: 0, 25, 100 and 500 ppm
Duration of Single Treatment: 6 h
Frequency of Treatment: 7 days/week
General Toxicity - Parent: NOAEC: > 500 ppm
General Toxicity F1: NOAEC: > 500 ppm
Early Embryonic Development: NOAEC: > 500 ppm
Result: No reproductive effects.

Effects on foetal development : Species: rat
Application Route: Inhalation
Dose: 0, 100, 500, 1000 or 2000 ppm
Duration of Single Treatment: 14 d
Frequency of Treatment: 6 hr/day
General Toxicity Maternal: NOAEC: 500 ppm
Teratogenicity: NOAEC: > 2,000
Developmental Toxicity: NOAEC: 100 ppm
Result: No teratogenic effects., Developmental toxicity occurred at maternal toxicity dose levels

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

Reproductive toxicity - Assessment : Animal testing did not show any effects on fertility. Damage to fetus not classifiable

STOT - single exposure

Product: No data available

Components:

1330-20-7:

Exposure routes:	Target Organs:	Assessment:	Remarks:
Inhalation	Respiratory system	May cause respiratory irritation., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.	

100-41-4: No data available

108-88-3: No data available

98-82-8: No data available

STOT - repeated exposure

Product: No data available

Components:

1330-20-7:

Exposure routes:	Target Organs:	Assessment:	Remarks:
	Liver, Kidney, Central nervous system	May cause damage to organs through prolonged or repeated exposure., The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.	

100-41-4: No data available

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

108-88-3:No data available

98-82-8:No data available

Repeated dose toxicity

Components:

1330-20-7:

Species: rat, male and female

NOAEL: 250 mg/kg

Application Route: Oral

Exposure time: 103 wk

Number of exposures: 5 d/wk

Dose: 0, 250 or 500 mg/kg

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Components:

1330-20-7:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

1330-20-7:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l
Exposure time: 24 h
Test Type: static test
Method: OECD Test Guideline 202

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata): 4.36 mg/l
 End point: Growth rate
 Exposure time: 72 h
 Test Type: static test
 Analytical monitoring: yes
 Method: OECD Test Guideline 201
 GLP: yes

Ecotoxicology Assessment
 Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

1330-20-7:

Biodegradability : Inoculum: activated sludge
 Result: Readily biodegradable.
 Biodegradation: 72 %
 Exposure time: 20 d

Bioaccumulative potential

Components:

1330-20-7:

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

108-88-3:

Partition coefficient: n-octanol/water : log Pow: 2.73

98-82-8:

Partition coefficient: n-octanol/water : log Pow: 3.55 (23 °C)

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S.

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

IATA (International Air Transport Association): UN1307, XYLENES, 3, III, Flash Point:27 °C(81 °F)

IMDG (International Maritime Dangerous Goods): UN1307, XYLENES, 3, III, Marine Pollutant (MIXED XYLENES, ETHYLBENZENE)

DOT (Department of Transportation): UN1307, XYLENES, 3, III

SECTION 15. REGULATORY INFORMATION

OSHA Hazards : Flammable liquid, Harmful by skin absorption., Moderate skin irritant, Moderate eye irritant, Moderate respiratory irritant, Aspiration hazard

WHMIS Classification : B2: Flammable liquid
D2A: Very Toxic Material Causing Other Toxic Effects
D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Mixed xylenes	1330-20-7	100	100

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Chronic Health Hazard
Acute Health Hazard

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

100-41-4	**Ethylbenzene	30 %
108-88-3	**Toluene	4.9999 %
98-82-8	**Cumene	1 %
71-43-2	**Benzene	0.02 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F). The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7	Mixed xylenes	100 %
100-41-4	**Ethylbenzene	30 %
108-88-3	**Toluene	4.9999 %
98-82-8	**Cumene	1 %
71-43-2	**Benzene	0.02 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7	Mixed xylenes	100 %
100-41-4	**Ethylbenzene	30 %
108-88-3	**Toluene	4.9999 %
71-43-2	**Benzene	0.02 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

1330-20-7	Mixed xylenes	100 %
100-41-4	**Ethylbenzene	30 %
108-88-3	**Toluene	4.9999 %
71-43-2	**Benzene	0.02 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

100-41-4	**Ethylbenzene	30 %
108-88-3	**Toluene	4.9999 %

US State Regulations

Massachusetts Right To Know

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

1330-20-7	Mixed xylenes	90 - 100 %
100-41-4	**Ethylbenzene	0 - 30 %
108-88-3	**Toluene	1 - 5 %
98-82-8	**Cumene	0.1 - 1 %
71-43-2	**Benzene	0 - 0.1 %

Pennsylvania Right To Know

1330-20-7	Mixed xylenes	90 - 100 %
100-41-4	**Ethylbenzene	0 - 30 %
108-88-3	**Toluene	1 - 5 %
98-82-8	**Cumene	0.1 - 1 %
71-43-2	**Benzene	0 - 0.1 %

New Jersey Right To Know

1330-20-7	Mixed xylenes	90 - 100 %
100-41-4	**Ethylbenzene	0 - 30 %
108-88-3	**Toluene	1 - 5 %
98-82-8	**Cumene	1 - 5 %

California Prop 65

	WARNING! This product contains a chemical known to the State of California to cause cancer.
100-41-4	**Ethylbenzene
98-82-8	**Cumene
71-43-2	**Benzene
	WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
108-88-3	**Toluene
71-43-2	**Benzene

The components of this product are reported in the following inventories:

United States TSCA Inventory	:	y (positive listing) (On TSCA Inventory)
Canadian Domestic Substances List (DSL)	:	y (positive listing) (All components of this product are on the Canadian DSL.)
Australia Inventory of Chemical Substances (AICS)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
New Zealand. Inventory of Chemical Substances	:	y (positive listing) (On the inventory, or in compliance)

Safety Data Sheet

Xylene

Version 1.6


Revision Date: 04/29/2015

		with the inventory)
Japan. ENCS - Existing and New Chemical Substances Inventory	:	y (positive listing) (On the inventory, or in compliance with the inventory)
Korea. Korean Existing Chemicals Inventory (KECI)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
China. Inventory of Existing Chemical Substances in China (IECSC)	:	y (positive listing) (On the inventory, or in compliance with the inventory)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

Legacy MSDS: R0004340, 100000006769

Material number:

16084135, 16075696, 16063696, 16056826, 16056828, 16056827, 16056829, 16056825, 16041807, 16040131, 16036781, 16017302, 16005979, 16000348, 781040, 776944, 763953, 710729, 710728, 708716, 707260, 706448, 638918, 623621, 568063, 554061, 554060, 554200, 508616, 508582, 508489, 70145, 70881, 70227, 70442, 53546, 70136, 102351, 102986, 102907, 102359, 87256, 86304, 53755, 69589, 103201, 53758, 85972, 103204, 86307, 102898, 69592, 70082, 85965, 54057, 70432, 86513, 102348, 102683, 102433, 86815, 103194, 69917, 508229, 508294, 508230, 502710, 39908, 22253, 22252, 22034, 22033, 20530, 20529, 20528, 20526, 20525, 20523, 20522, 20524

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act

Safety Data Sheet

Xylene

Version 1.6

Revision Date: 04/29/2015

	es		
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		