

DESCRIPTION and USES

Deck & Dock Wood Protector is a water-repellent treatment used to help beautify and protect new or weathered bare wood. It can be used on all types of exterior lumber to prevent the damaging effects of moisture such as splitting, swelling, and warping. It also helps prevent the growth of mildew, fungus, and algae. **Deck & Dock Wood Protector** provides UV protection to help resist fading and discoloration for a variety of semi-transparent colors. **Deck & Dock Clear** allows the wood to gray naturally while limiting UV damage.

PREPARATION

SURFACE PREPARATION: All cutting, gluing, and sanding of the wood should be done before coating. Surfaces to be stained must clean, dry, and free of contaminants such as dirt, oil or wax. If mildew is present, clean the surface with 1 part household bleach to 10 parts water solution. New pressure-treated wood should be allowed to dry for at least 30 days. New cedar should have the mill glaze removed through sanding or an oxalic acid-based cleaning/brightener product. Discoloration can be removed and the wood restored to its natural color by using a wood brightener. Rinse well after these treatments. Wear protective gloves, clothing, and goggles when working with bleach or wood brightener. Power washing to remove old or peeling stain is recommended. Allow 2 days for wood to dry after rain, rinsing, or power washing before staining.

APPLICATION

Stir thoroughly before and occasionally during use. Stains are best applied with a natural bristle brush, paint pad, or special stain applicator. Rolling and spraying may also be used, but the stain should be worked into the pores of the wood with a brush immediately after to avoid puddling and over application. Maintain a wet edge by staining only a few boards at a time. Apply one coat only for best results. Do not thin. Apply at temperatures above 40°F and avoid direct sunlight. Protect surrounding area from drips and spills. Yearly maintenance coats should be applied on horizontal surfaces and every 2-3 years on vertical surfaces to maintain ideal appearance.

CLEAN UP

Clean tools immediately after use with specified clean up solvent. Use same clean up solvent to clean dried product off equipment.

COLORS

A full range of custom colors are available.

REGULATORY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Flat
Vehicle Type:	Alkyd
Weight Solids:	37-39%
Volume Solids:	32-33%
Density:	7.2-7.5 lb/gal
Coverage:	100 – 150 SF/Gallon
Dry Time:	
<i>Touch:</i>	3 hours
<i>Full Cure:</i>	24 hours
Clean Up:	Mineral Spirits
VOC:	<550 g/L

Consult with a RepcoLite representative for additional recommendations of cleaners and brightening products.

PRODUCT CODE INFORMATION

00535	Deck & Dock Clear – Gallon
00536	Deck & Dock Cedar – Gallon
00537	Deck & Dock Cypress – Gallon
00538	Deck & Dock Butternut – Gallon
00539	Deck & Dock Mahogany – Gallon
00544	Deck & Dock Clear – 5 Gallon
00543	Deck & Dock Cedar – 5 Gallon
00542	Deck & Dock Cypress – 5 Gallon
00541	Deck & Dock Butternut – 5 Gallon
00540	Deck & Dock Mahogany – 5 Gallon