

DESCRIPTION and USES

Port City Topside Bilge Paint is a semi-gloss urethane alkyd designed to provide boats and watercraft with superior adhesion, water resistance, and exceptional abrasion protection. With excellent color and gloss retention, it ensures a durable finish. Formulated to flow and self-level effortlessly, it creates a smooth, professional-grade coating, making it ideal for protecting the interior surfaces of a hull. **NOT INTENDED FOR ARCHITECTURAL USE.**

PREPARATION

Surface Preparation: All surfaces must be dry and free of dirt, grease, rust and loose paint. Rough surfaces should be smoothed with sandpaper. Glossy surfaces must be sanded to remove the gloss and wiped clean. Patch all holes and cracks with suitable materials prior to painting.

APPLICATION

Stir thoroughly before and occasionally during use. Apply with a brush or roller making sure all areas, especially edges, are well coated. Maintain a wet edge during application to avoid lap lines. Avoid application, if possible, when temperatures are above 90°F or below 50°F or when relative humidity is above 85%.

CLEAN UP

Clean painting tools immediately after use with specified clean up solvent. Use same clean up solvent to clean dried product off equipment.

COLORS

Available in Mahogany Bilge and Gray Bilge.

REGULATORY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

TECHNICAL DATA

Finish:	Semi-Gloss
Vehicle Type:	Alkyd/Urethane
Weight Solids:	65-67%
Volume Solids:	48-49%
Density:	9.6-10.0 lb/gal
Coverage:	400-450 SF/Gallon
Dry Time:	
<i>Touch:</i>	4 hours
<i>Recoat:</i>	8 hours
Clean Up:	Paint Thinner (Mineral Spirits)
VOC:	< 400 g/L
Compliance:	As of 08/04/2025
	Federal: No
	OTC Phase 1: No
	OTC Phase 2: No
Not Intended for Architectural Use.	

Consult with a RepcoLite representative for additional recommendations of primers.

PRODUCT CODE INFORMATION

00626	Port City Topside Bilge Paint – Mahogany Bilge
00617	Port City Topside Bilge Paint – Gray Bilge

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.