

## DESCRIPTION and USES

A tough, wear-resistant finish for wood, metal or concrete floors. The hard, smooth finish of this product gives an attractive and easily cleaned floor surface. Suitable for interior use on floors, stairs and covered patios and porches. Not recommended for use on wood decks.

## SURFACE PREPARATION

All surfaces must be dry and free of dirt, grease and loose paint. Rough surfaces should be smoothed with sandpaper. All new or unpainted concrete floors must be treated with a 25% solution of muriatic acid in water to remove unreacted cement and to promote paint adhesion. Rinse floor well after acid treatment and allow to dry completely. Allow new concrete floors to cure 30 days before painting. Previously painted surfaces, if glossy, should be sanded to assure paint adhesion.

## APPLICATION

Apply with brush, roller or pad applicator. Do not apply thick coats; thin coats will dry faster and harder. Do not apply when temperatures are below 50°F or above 90°F. In areas where foot slipping may occur, such as steps or stairs, the addition of a non-slip additive is recommended. Thinning this product will bring it out of compliance with current VOC regulations. DO NOT THIN.

## SAFETY INFORMATION

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

## COLORS

Battleship Gray, Stone, Granite, Medium Gray, New Silver Gray, Sandstone, Tile Green, Tile Red & Walnut Brown. Light to Medium tone custom colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

## TECHNICAL DATA

|                       |  |
|-----------------------|--|
| <b>Finish:</b>        | Medium Gloss   |
| <b>Vehicle Type:</b>  | Alkyd/Urethane   |
| <b>Volume Solids:</b> | 47%  |
| <b>Coverage:</b>      | 400 – 450 SF/Gallon                                    |
| <b>Dry Time:</b>      |  |
| <i>Recoat:</i>        | 6 – 8 Hours  |
| <i>Hard:</i>          | 12 – 16 Hours  |
| <i>Full Hardness:</i> | 4 – 6 Days   |
| <b>Primer:</b>        |  |
| <i>Masonry:</i>       | 44610 Sprayable Block Filler                           |
| <i>Drywall:</i>       | 44410 Quick Sealer                                     |
| <i>Plaster:</i>       | 44110 Prime-All WB Primer                              |
| <i>Galvanized:</i>    | 44810 QD Rust Inhibitive Primer                        |
| <i>Steel:</i>         | 44917 Metl-Clad Metal Primer                           |
| <i>Wood:</i>          | 44010 Pro-Flo Primer-Undercoater<br>44510 Zip Prime-WB |
| <b>VOC:</b>           | Less than 400 g/l                                      |
| <b>Clean Up:</b>      | Paint Thinner (Mineral Spirits)                        |

## PRODUCT CODE INFORMATION

|       |                                       |
|-------|---------------------------------------|
| 40302 | Urethane Floor Enamel—192 Base        |
| 40303 | Urethane Floor Enamel—193 Base        |
| 40312 | Urethane Floor Enamel—Stone           |
| 40313 | Urethane Floor Enamel—Granite         |
| 40314 | Urethane Floor Enamel—Sandstone       |
| 40315 | Urethane Floor Enamel—New Silver Gray |
| 40317 | Urethane Floor Enamel—Battleship Gray |
| 40320 | Urethane Floor Enamel—Tile Red        |
| 40340 | Urethane Floor Enamel—Tile Green      |
| 40350 | Urethane Floor Enamel—Walnut Brown    |

**Repcolite Paints, Inc.**

473 W. 17<sup>th</sup> St.

Holland, MI 49423

(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)