

## DESCRIPTION and USES

**Glo-Enamel-WB Interior/Exterior Gloss Enamel** is a superior quality enamel that uses the latest in waterborne technology to provide a durable, stain resistant, and washable finish for interior surfaces and a color retentive and weather-resistant coating for exterior surfaces. It has very good wet and dry adhesion to most clean, paintable surfaces. The very low solvent content reduces environmental and human health risks. This product is not intended to be used in corrosive atmospheres or for immersion service. **Glo-Enamel-WB** is intended for use on all properly prepared materials used in may be used as a primer and paint all-in-one, but in certain circumstances the use of a suitable primer is desirable.

## SURFACE PREPARATION

All surfaces to be painted must be dry and free from dirt, oil, and other contamination. Loose and peeling paint must be removed to provide a sound surface. Patching and caulking should be done prior to painting. Prime all unpainted surfaces, if necessary, with a suitable primer. Rusty or bare metal must be primed with Metl-Clad 449 Metal Primer.

## APPLICATION

Apply with a quality paint brush or roller. Airless spray may also be used. It is important to maintain a wet edge while painting. Avoid brushing back into partially dried paint. Avoid painting on hot surfaces or in direct sunlight. High humidity will slow the dry time of this product significantly, therefore do not paint when heavy dew or rain is expected. Paint dries best between 65° to 85° F. Do not apply at temperatures below 60° F. Allow 2 to 4 hours dry time before recoating. For best coverage apply at a maximum of 400 square feet per gallon. Rough or textured surfaces will require more paint. Thinning this product is normally not necessary, however, if thinning is required use only clean water.

## CLEAN UP

Clean painting tools immediately after use with warm, soapy water. Wipe up spills before they dry with a damp cloth.

## SAFETY INFORMATION

For complete safety information, refer to the Safety Data Sheet for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

## TECHNICAL DATA

<b>Finish:</b>	Semi-Gloss
<b>Vehicle Type:</b>	100% Acrylic Latex
<b>Volume Solids:</b>	34%
<b>Coverage:</b>	400 – 450 SF/Gallon
<b>Dry Time:</b>	
<i>Touch:</i>	30 Minutes
<i>Recoat:</i>	2 Hours
<i>Full Hardness:</i>	72 Hours

### Primer:

<i>Masonry:</i>	44610 Sprayable Block Filler
<i>Drywall:</i>	44410 Quick Sealer
<i>Plaster:</i>	44110 Prime-All
	44010 Pro-Flo Primer-Undercoater
<i>Metal:</i>	44810 QD Rust Inhibitive Primer
<i>Ferrous Metals:</i>	44917 Met'l Clad Primer
<i>Wood (Exterior):</i>	44510 Zip Prime-WB
<i>Wood (Interior):</i>	44010 Pro-Flo Primer-Undercoater
<b>VOC:</b>	Less than 150 g/L
<b>Clean Up:</b>	Water

## COLORS

Available in white and pastel colors.

## PRODUCT CODE INFORMATION

41210	Glo-Enamel-WB Semi-Gloss—White
-------	--------------------------------

### RepcoLite Paints, Inc.

473 W. 17<sup>th</sup> St.

Holland, MI 49423

(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)