

### DESCRIPTION and USES

This premium quality paint provides a tough, durable, smooth low-luster finish that will withstand repeated washing. It combines high hiding and easy application. It's jelled consistency minimizes drips and spatters. This paint is ideal for walls, ceilings, woodwork and other interior surfaces that require a fine quality, durable finish.

### SURFACE PREPARATION

All surfaces must be dry, free of grease, wax, and dirt. All rough surfaces should be sanded smooth. Degloss all high gloss surfaces with sandpaper or a liquid deglosser to ensure adhesion. Prime all bare surfaces with the recommended primer.

### APPLICATION

This paint can be applied with a brush, roller or spray gun. For best results, do not apply when temperatures are below 55°F or above 90°F. Thinning this product will bring it out of compliance with current VOC regulations. DO NOT THIN.

### SAFETY INFORMATION

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

### COLORS

This product is available in white, all RepcoLite *Soft Whites* and light *Color Folio* and *Color Studio* Colors. No tint base, deep base or accent base available.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

### TECHNICAL DATA

<b>Finish:</b>	Low Gloss
<b>Vehicle Type:</b>	Soya Alkyd
<b>Volume Solids:</b>	50%
<b>Coverage:</b>	400 – 450 SF/Gallon
<b>Dry Time:</b>	
<i>Touch:</i>	4 – 6 Hours
<i>Recoat:</i>	12 – 16 Hours
<b>Primer:</b>	
<i>Masonry:</i>	44610 Sprayable Block Filler
<i>Drywall:</i>	44410 Quick Sealer
<i>Plaster:</i>	44010 Pro-Flo Primer-Undercoater 44110 Prime-All WB Primer
<i>Steel:</i>	44917 Metl-Clad Metal Primer
<i>Wood:</i>	44010 Pro-Flo Primer-Undercoater 44210 Zip Prime
<b>VOC:</b>	Less than 380 g/l
<b>Clean Up:</b>	Paint Thinner (Mineral Spirits)

### PRODUCT CODE INFORMATION

41610	Beauti-Color Satin Sheen—White
-------	--------------------------------

**RepcoLite Paints, Inc.**  
473 W. 17<sup>th</sup> St.  
Holland, MI 49423  
(616) 396-1275  
[www.repcolite.com](http://www.repcolite.com)