

### DESCRIPTION and USES

This product is designed to provide one coat blackout hiding over all types of interior wall and ceiling surfaces. Overspray from this paint dries quickly to a harmless powder that can be easily removed by vacuuming or sweeping.

### SURFACE PREPARATION

Generally, a minimum of surface preparation is needed when using this product. However, the surface must be free of loose dirt, peeling paint, and grease. Air blast cleaning is usually the preferred method of surface preparation.

### APPLICATION

Apply with airless or air spray only. This product is not suitable for use with brush or roller. Because of the high volume of this product used during painting, fumes will build up rapidly in confined areas. Use with adequate ventilation to avoid potential fire and health problems from these fumes. Apply when air and surface temperatures are above 50°F. Temperature of surfaces to be painted must be at least 50°F above the dew point to prevent moisture condensation on the surface. In order to maintain compliance with current VOC regulations, DO NOT THIN this product.

### SAFETY INFORMATION

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

### COLORS

This product is available in white, black and light tone colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

### TECHNICAL DATA

<b>Finish:</b>	Flat
<b>Vehicle Type:</b>	Soya Alkyd
<b>Volume Solids:</b>	
<b>Coverage:</b>	200 – 300 SF/Gallon
<b>Dry Time:</b>	
<i>Touch:</i>	30 Minutes (under normal conditions, spray mist will be dry in a 12' – 14' drop from ceiling to floor.)
<b>Primer:</b>	
<i>Masonry:</i>	Self Prime
<i>Drywall:</i>	44410 Quick Sealer
<i>Plaster:</i>	44110 Prime-All WB Primer
<i>Steel:</i>	44917 Metl-Clad Metal Primer
<i>Wood:</i>	Self Prime
<b>VOC:</b>	Less than 400 g/l
<b>Clean Up:</b>	VMP Naptha

### PRODUCT CODE INFORMATION

42510	Dry Mist Alkyd Flat—White
42570	Dry Mist Alkyd Flat—Black

**RepcoLite Paints, Inc.**  
473 W. 17<sup>th</sup> St.  
Holland, MI 49423  
(616) 396-1275  
[www.repcolite.com](http://www.repcolite.com)