

DESCRIPTION and USES

ProSelect Plus is our premium professional line of paint, emphasizing hiding power and excellent application characteristics at an economical price. It is ideal for residential, commercial, and industrial painting. It can be used on drywall, plaster, and masonry surfaces. It is intended for interior use on walls and ceilings. This product meets VOC requirements for use in LEED construction.

SURFACE PREPARATION

All surfaces to be painted must be free of dirt, grease, wax or other contaminants. All new surfaces should be primed with the recommended primer, allowing sufficient drying time before recoating. All glossy surfaces must be dulled by sanding with 120-grit sandpaper.

APPLICATION

Apply with synthetic bristle brush, roller or airless spray. For airless spray, use .015 - .019 tip adjusting pressure as needed. Do not apply at temperatures below 60°F.

SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

This product is available in white and light to medium tone colors. No deep tone or accent colors are available.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Flat
Vehicle Type:	Vinyl-Acrylic
Volume Solids:	48%
Coverage:	400 – 450 SF/Gallon
Dry Time:	
<i>Touch:</i>	30 – 60 Minutes
<i>Recoat:</i>	2 Hours
Primer:	
<i>Drywall:</i>	44310 ProSelect Latex Wall Sealer
<i>Plaster:</i>	44110 Prime-All WB Primer
<i>Masonry:</i>	44610 Block Filler or Self Prime
<i>Metal:</i>	44917 Metl-Clad Metal Primer
<i>Wood:</i>	44010 Pro-Flo Primer-Undercoater 44110 Prime-All WB Primer
VOC:	57 g/l
Clean Up:	Water

PRODUCT CODE INFORMATION

43010

ProSelect Plus Ceiling White

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com