

### DESCRIPTION and USES

This product is part of the HALLMARK line of premium interior water borne finishes that provide a level of performance ordinary latex paints cannot match. This Flat Enamel features easy, no spatter application, water clean up, fast dry and low odor. Flat Enamel produces a beautiful velvet flat finish that can withstand repeated washings. Flat Enamel can be used on all properly prepared and primed construction materials in both residential and commercial buildings. This product meets VOC requirements for use in LEED construction.

### SURFACE PREPARATION

All surfaces to be painted must be free of dirt, grease, wax or other contaminants. All new surfaces should be primed with the recommended primer, allowing sufficient dry time before recoating. All glossy surfaces must be dulled by sanding with #120 grit sandpaper.

### APPLICATION

Apply with a synthetic bristle brush, roller or airless spray. Do not apply at temperatures below 60°F.

### SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

### COLORS

This product is available in white and all *Color Studio* and *Color Folio* Colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

### TECHNICAL DATA

<b>Finish:</b>	Satin Flat
<b>Vehicle Type:</b>	Vinyl Acrylic
<b>Pigments:</b>	Titanium Dioxide & Functional Pigments
<b>Volume Solids:</b>	39%
<b>Coverage:</b>	400 – 450 SF/Gallon
<b>Dry Time:</b>	
<i>Touch:</i>	30 Minutes
<i>Recoat:</i>	3 Hours
<b>Primer:</b>	
<i>Masonry:</i>	44610 Sprayable Block Filler
<i>Drywall:</i>	44410 Quick Sealer
<i>Plaster:</i>	44110 Prime-All WB Primer
<i>Non-Ferrous Metals:</i>	44810 QD Rust Inhibitive Primer
<i>Ferrous Metals:</i>	44917 Metl-Clad Metal Primer
<i>Wood (Interior):</i>	44010 Pro-Flo Primer-Undercoater 44110 Prime-All WB Primer
<b>VOC:</b>	104 g/l
<b>Clean Up:</b>	Water

### PRODUCT CODE INFORMATION

43110	Hallmark Flat Enamel—White
43102	Hallmark Flat Enamel—292 Base

**RepcoLite Paints, Inc.**  
473 W. 17<sup>th</sup> St.  
Holland, MI 49423  
(616) 396-1275  
[www.repcolite.com](http://www.repcolite.com)