

DESCRIPTION and USES

This primer is designed for use on new interior wood. It features rapid dry and easy sanding characteristics, making it an excellent choice for interior wood and MDF trim. It is not recommended for glossy or sealed surfaces, metal or plastic. This primer may crack when applied to flexible surfaces such as caulk. This product meets VOC requirements for use in LEED construction.

SURFACE PREPARATION

All surfaces to be primed must be clean and dry. Sand new wood with 120-grit sandpaper. Patch all holes and cracks before priming.

APPLICATION

Apply with a synthetic bristle brush, paint roller or airless spray. Do not apply at temperatures below 60°F. Sand off all surface roughness that may appear after primer is dry with 180 or 220-grit sandpaper.

SAFETY INFORMATION

For complete safety information, refer to the MATERIAL SAFETY DATA SHEET for this product.

COLORS

White. (May be tinted with up to 4 oz. of Universal Colorant per gallon.)

TECHNICAL DATA

Vehicle Type:	100% Acrylic Latex
Volume Solids:	62%
Coverage:	250 – 350 SF/Gallon
Dry Time:	
<i>Touch:</i>	20 – 40 Minutes
<i>Recoat:</i>	1 Hour for latex top coats
VOC:	54 g/l
Clean Up:	Water

PRODUCT CODE INFORMATION

44114 EZ-Prime Waterborne Interior Primer

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. Repolite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

Repolite Paints, Inc.
473 W. 17th St.
Holland, MI 49423
(616) 396-1275
www.repolite.com