

DESCRIPTION and USES

This fast drying, latex based sealer is designed to seal porous interior construction materials such as drywall, acoustical tile, plaster and poured concrete walls. It is the sealer of choice for drywall because it will not raise the paper fibers of the wallboard. It provides excellent holdout for gloss and semi-gloss top coats. It can be used under both latex and oil based finish coats. This product meets VOC requirements for use in LEED construction.

SURFACE PREPARATION

All surfaces to be painted must be dry and free of dust and dirt. This paint will not block out water stains, use 44210 ZIP PRIME or 44510 ZIP PRIME WB for this purpose. When this product is used over previously painted surfaces, sanding is recommended to ensure adhesion.

APPLICATION

Apply with synthetic bristle brush, roller or airless spray. When airless spray is used, back rolling is recommended to even out paint application. Do not apply at temperatures below 60°F.

SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

White (May be tinted with up to 4 oz. Universal Colorant. For darker colors, use 44404 QUICK SEALER – DEEP BASE).

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Vehicle Type:	Vinyl Acrylic Latex
Volume Solids:	41%
Coverage:	300 – 350 SF/Gallon on smooth surfaces
Dry Time:	
<i>Touch:</i>	30-45 Minutes
<i>Recoat:</i>	4 Hours (high humidity will increase dry time)
VOC:	55 g/l
Clean Up:	Water

PRODUCT CODE INFORMATION

44410 Quick Sealer – White

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com