



# Wallboard Smoother

*Interior Wall Primer*

**Product Data Sheet**

## DESCRIPTION and USES

This product is designed for application to new bare drywall in situations where hiding of tape joints or other surface imperfections is necessary. It will prevent these imperfections from being visible after the top coat is applied. It features excellent leveling characteristics and serves as the primer coat. This product meets VOC requirements for use in LEED construction.

## SURFACE PREPARATION

All surfaces to be primed must be clean and dry. Remove sanding dust from the surface by vacuuming or sweeping.

## APPLICATION

This product is best applied by airless spray. Brush and roller application is possible, but build will be lower and ideal leveling characteristics will be reduced. Do not apply at temperatures below 60°F. Sand primer surface with 150-grit sandpaper if necessary to remove surface roughness.

## SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

## COLORS

White (May be tinted with up to 4 oz. of Universal Colorant per gallon).

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

## TECHNICAL DATA

<b>Vehicle Type:</b>	PVA Latex
<b>Volume Solids:</b>	61%
<b>Coverage:</b>	50 – 100 SF/Gallon
<b>Dry Time:</b>	
<i>Touch:</i>	45 – 60 Minutes
<i>Recoat:</i>	2 – 3 Hours
<b>VOC:</b>	54 g/l
<b>Clean Up:</b>	Water

## PRODUCT CODE INFORMATION

44605                      Wallboard Smoother

**RepcoLite Paints, Inc.**

473 W. 17<sup>th</sup> St.

Holland, MI 49423

(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)