

## DESCRIPTION and USES

This primer is a special blend of linseed oil, alkyd resins and pigments that effectively penetrates and seals new wood or previously painted surfaces. It also stops extractive bleeding of stains from redwood and cedar. It is a universal primer designed for use under both latex and oil-based finish coats. May be tinted with universal colorant (up to 6 oz. per gallon) to approximate finish color.

## SURFACE PREPARATION

All surfaces to be primed must be dry and free of dust and dirt. All peeling or flaking old paint must be removed by scraping.

## APPLICATION

Best applied with a paint brush or roller, however, spray application may be used when circumstances allow. Do not apply at temperatures below 40°F or above 85°F or when rain is expected before primer is dry to the touch. Low temperatures will significantly increase the dry time of this product. Do not recoat until completely dry. Use as supplied. DO NOT THIN.

## CLEAN UP

Clean painting tools immediately after use with Paint Thinner (Mineral Spirits).

## SAFETY INFORMATION

**NOTICE:** Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. For complete safety information, refer to the MATERIAL SAFETY DATA SHEET for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

## TECHNICAL DATA

<b>Vehicle Type:</b>	Soya Alkyd Resins and Linseed Oil
<b>Volume Solids:</b>	61.70%
<b>Coverage:</b>	350 – 400 SF/Gallon (depending on surface porosity.)
<b>Dry Time:</b>	
<i>Touch:</i>	6 – 8 Hours
<i>Recoat:</i>	24 Hours
<b>VOC:</b>	Less than 350 g/l
<b>Clean Up:</b>	Paint Thinner (Mineral Spirits)

## PRODUCT CODE INFORMATION

44710 #65 Exterior Primer—White

**RepcoLite Paints, Inc.**

473 W. 17<sup>th</sup> St.

Holland, MI 49423

(616) 396-1275

[www.repcolite.com](http://www.repcolite.com)