

Metl-Clad QD Primer

Rust Resistant Red Oxide Shop Primer

Product Data Sheet

DESCRIPTION and USES

A fast drying primer for use on structural steel. Provides protection to metal for up to 6 months of exterior exposure. Also suitable as a surfacing primer under implement enamels. This product provides only a limited amount of rust inhibition. Where maximum rust inhibition is desired, use 44917 Metl Clad Primer or 44810 Quick Dry Metl Clad Primer.

SURFACE PREPARATION

All surfaces to be primed must be dry and free of dust, dirt and oil or grease. Rusted areas should be wire brushed to remove granular rust.

APPLICATION

Apply with airless or air spray only. Do not apply at temperatures below $40^{\circ}F$.

NOTICE: This product is intended for industrial use only. It is not suitable for or intended for architectural use.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

Red

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Vehicle Type:

Volume Solids: 32%

Coverage:

Dry Time:

 Touch:
 30 Minutes

 Recoat:
 2 Hours

 VOC:
 560 g/l

 Clean Up:
 Xylene

PRODUCT CODE INFORMATION

44820 Red Rust Resistant Shop Primer

RepcoLite Paints, Inc.

473 W. 17th St. Holland, MI 49423 (616) 396-1275 www.repcolite.com