



Premium Bonding Primer

Quick Dry White

Product Data Sheet

DESCRIPTION and USES

Premium Bonding Primer is a quick drying, versatile primer that has many uses. It is an excellent adhesion promoting primer for use on metal, wood, hardboard, tile, many types of plastic, and other surfaces that are difficult to adhere to. It is not intended for use on flexible surfaces such as rubber or silicone caulk, and should not be used in situations where extended periods of submersion in water will occur. **Premium Bonding Primer** may be used under all oil-based and latex top coats as well as epoxies and lacquers. Prior to doing a complete job, testing a smaller area for compatibility with the surface and finish coats is advised.

PREPARATION

All surfaces must be dry and free of dirt, grease, rust and loose paint. Rough surfaces should be smoothed with sandpaper. Glossy surfaces must be sanded to remove the gloss. Patching and caulking should be done prior to painting.

APPLICATION

Apply with airless or air-assisted spray. Small areas may be rolled or brushed. Do not apply at temperatures below 40°F. Use as supplied. Do not thin.

CLEAN UP

Clean painting tools immediately after use with specified clean up solvent. Use same clean up solvent to clean dried product off equipment.

COLORS

Supplied in White. Light to medium custom colors are available. Use RepcoLite's Alkyd Solvent-borne Color System.

REGULATORY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

TECHNICAL DATA

Finish:	Flat
Vehicle Type:	Phenolic Alkyd Resin
Weight Solids:	67-68%
Volume Solids:	49-50%
Density:	11.5-11.6 lb/gal
Coverage:	300-400 SF/Gallon
Dry Time:	
<i>Touch:</i>	20-30 minutes
<i>Recoat:</i>	1 Hour on porous surfaces 2-3 Hours on non-porous surfaces
Clean Up:	Xylene
VOC:	< 450 g/L
Compliance:	As of 01/30/2025
	Federal: Yes
	OTC Phase 1: No
	OTC Phase 2: No
Topcoat:	All Waterborne Topcoats All Solvent-borne Topcoats

Consult with a RepcoLite representative for additional recommendations of topcoats

PRODUCT CODE INFORMATION

44830 Premium Bonding Primer

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

RepcoLite Paints, Inc. 473 W 17th St. Holland, MI 49423
(616) 396-1275 www.repcolite.com