

DESCRIPTION and USES

This paint is a true one-coat house paint that features excellent hiding, gloss and color retention and durability. It is designed for use on wood or metal siding and trim. Its gloss finish resists dirt pickup and washes easily. It combines highly durable pigments with specially processed alkyd resin and linseed oil to provide the latest and best in oil-based exterior paint technology. It is designed for use on wood or metal siding and trim. It is particularly suitable for use on older homes and for restoration work on historic buildings.

SURFACE PREPARATION

All surfaces to be painted must be dry and free of dirt. Bare wood or metal should be primed with recommended primer. Protected areas, such as under eaves, should be washed with detergent and water, rinsed and allowed to dry. Remove all loose and peeling paint by scraping.

APPLICATION

Apply with a paint brush, roller or pad applicator. Avoid painting in direct sun or when rain or heavy dew is expected. Significantly longer dry times should be anticipated in cool or cold weather.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

White, *Color Folio* and *Color Studio* Colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Gloss
Vehicle Type:	Soya Alkyd Resins and Linseed Oil
Volume Solids:	74%
Coverage:	400 – 450 SF/Gallon (on smooth surfaces).
Dry Time:	
<i>Touch:</i>	8 – 12 Hours
<i>Recoat:</i>	24 Hours (Temperatures below 60°F will lengthen the dry time).
Primer:	
<i>Metal:</i>	44917 Metl-Clad Metal Primer
<i>Wood:</i>	44710 #65 Exterior Primer
VOC:	Less than 380 g/l
Clean Up:	Paint Thinner (Mineral Spirits)

PRODUCT CODE INFORMATION

45410	Super-One House Paint—White
45402	Super-One House Paint—132 Base
45403	Super-One House Paint—133 Base
45406	Super-One House Paint—136 Base

RepcoLite Paints, Inc.

473 W. 17th St.
Holland, MI 49423
(616) 396-1275
www.repcolite.com