

DESCRIPTION and USES

The WOODMASTER line of oil based stains is available in two types: Solid Color - This stain provides a rich velvety look to new or previously stained wood. It hides the grain and color of the wood but allows the texture of the wood to remain. It covers solidly in one coat so color changes are easily accomplished. Recommended for vertical surfaces of all commonly used exterior woods.

Transparent - This stain enhances the grain and texture of the wood surfaces to which it is applied. It penetrates deeply into the wood to provide lasting protection from sun and moisture. Ideal for both horizontal and vertical surfaces constructed of redwood, cedar or treated lumber. Not recommended for fir plywood.

SURFACE PREPARATION

Surfaces to be stained must be dry and clean. Old flaking stain should be removed by wire brushing.

APPLICATION

Apply with a brush, pad applicator or rough surface painting tool. Roller or spray application may be used, providing stain is brushed over to work it into the pores of the wood. Avoid staining in direct sun or when rain or heavy dew is anticipated. Maintain a wet edge by staining only a few boards from side to side or top to bottom. Occasionally, a slight gloss may develop when stain is applied over a sealed surface. This gloss or sheen will disappear over a few months exposure to the weather. Stir all stain products well before and during use. Thinning this product will bring it out of compliance with current VOC regulations. DO NOT THIN.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Flat
Vehicle Type:	Soya Alkyd Resins and Linseed Oil
Volume Solids:	54%
Coverage:	150 – 300 SF/Gallon (depending on surface porosity).
Dry Time:	
<i>Touch:</i>	8 Hours
Primer:	
<i>Wood:</i>	Self Prime
VOC:	Less than 350 g/l
Clean Up:	Paint Thinner (Mineral Spirits)

COLORS

White, RepcoLite *Color Folio* and *Color Studio* Colors.

PRODUCT CODE INFORMATION

45810	Woodmaster Oil Stain—White
45802	Woodmaster Oil Stain—2 Base
45803	Woodmaster Oil Stain—3 Base
45804	Woodmaster Oil Stain—4 Base
45806	Woodmaster Oil Stain—6 Base
45809	Woodmaster Oil Stain—9 Base (Semi-Trans)

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com