

DESCRIPTION and USES

This 100% acrylic paint will provide a durable finish on exterior vertical surfaces. It offers superior fade resistance, optimized mold and mildew control, and low temperature cure (as low as 36°F). It is self-priming and is low VOC. endura Satin Sheen is a premium exterior paint for use on vinyl, trim, metal, masonry and many other surfaces where a long-lasting finish is required. With proper preparation, this product may be used on aluminum or vinyl siding. Surface dirt is easily washed off this tough 100% acrylic finish paint. This paint dries quickly and tools are easily cleaned after use with soap and water.

SURFACE PREPARATION

All surfaces to be painted must be clean and free of standing water. Slightly damp surfaces can be painted. All bare surfaces must be primed with the recommended primer. Previously painted surfaces should be washed thoroughly to remove chalk and dirt. New poured or precast concrete should be treated with a 10% solution of Muriatic Acid in water to remove unreacted cement.

APPLICATION

Apply with a brush, roller or airless spray. During warm, windy weather dampening the surfaces with a mist of water will aid application. Avoid painting on hot surfaces or direct sunlight.

CLEAN UP

Clean painting tools immediately after use with warm, soapy water. Wipe up spill before they dry with a damp cloth.

SAFETY INFORMATION

For complete safety information, refer to the MATERIAL SAFETY DATA SHEET for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Satin Sheen
Vehicle Type:	100% Acrylic Latex
Volume Solids:	36%
Coverage:	200 – 400 SF/Gallon (depending on surface porosity.)
Dry Time:	
<i>Touch:</i>	45 Minutes
<i>Recoat:</i>	4 Hours (recoat times can be affected by differences in temperature and humidity).
Primer:	
<i>Brick/Block:</i>	44612 Acrylic Block Filler
<i>Poured Concrete:</i>	Self Prime (see SURFACE PREPARATION)
<i>Ferrous Metal:</i>	44917 Metl-Clad Primer
<i>Non-ferrous Metal:</i>	44810 Metl-Clad QD Primer
	44510 Zip Prime-WB
<i>Plastic:</i>	44510 Zip Prime-WB
<i>Wood:</i>	44710 #65 Exterior Primer
	44510 Zip Prime-WB
VOC:	75 g/l
Clean Up:	Water

PRODUCT CODE INFORMATION

46210	endura Satin Sheen—White
46202	endura Satin Sheen—322 Base
46203	endura Satin Sheen—323 Base
46206	endura Satin Sheen—326 Base

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com