

DESCRIPTION and USES

This exterior wood stain provides a rich, velvety finish on new or previously stained wood. It combines durable pigments and 100% acrylic resin for maximum durability and alkyd resins to penetrate and protect the wood. While this stain hides the color and grain of the wood, it allows the texture of the wood to remain. It's excellent covering ability makes it ideal for use when color changes are made. This stain has very good weather resistance, color retention and ease of application. It is ideal for use in restraining previously stained surfaces in good condition. Do not use on horizontal surfaces such as decks and furniture.

SURFACE PREPARATION

All surfaces to be stained must be clean and free of standing water. Damp surfaces can be successfully stained. During warm, windy weather, dampening the surface with a mist of water will aid application. Badly weathered surfaces should be stained with WOODMASTER Oil-Based Stain. When staining new cedar or redwood, test a small area for extractive bleeding of tannin stain. If extractive bleeding occurs, use WOODMASTER Oil-Based Stain.

APPLICATION

Apply with a brush or pad applicator, working stain into the surface. Avoid application on hot surfaces, in direct sun or when rain or heavy dew is expected within 4 hours. Try to maintain a wet edge by staining only a few boards side to side or top to bottom. Do not apply when air or surface temperature is below 50°F.

SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

White, RepcoLite *Color Folio* and *Color Studio* Colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Flat
Vehicle Type:	100% Acrylic
Volume Solids:	30%
Coverage:	150 – 300 SF/Gallon (depending on surface porosity).
Dry Time:	
<i>Touch:</i>	30 Minutes
<i>Recoat:</i>	4 Hours
VOC:	Less than 350 g/l
Clean Up:	Water

PRODUCT CODE INFORMATION

46810	Woodmaster Latex Stain—White
46802	Woodmaster Latex Stain—12 Base
46803	Woodmaster Latex Stain—13 Base
46804	Woodmaster Latex Stain—14 Base
46806	Woodmaster Latex Stain—16 Base

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com