

DESCRIPTION and USES

Saddle Ridge Equine Paint is an exterior wood stain designed for stables, fences, and other areas where horses and other livestock are kept. By incorporating the most bitter compound known, it discourages animals from chewing the wood and helps extend the lifespan of structural wood enclosures. Additionally, it provides a rich, velvety finish on new or previously stained wood. While **Saddle Ridge Equine Paint** hides the color and grain of the wood, it allows the texture of the wood to remain. This stain has very good ease of application. **Saddle Ridge Equine Paint** is not recommended for use on horizontal surfaces such as decks and furniture.

PREPARATION

Surface Preparation: All cutting, gluing, and sanding of the wood should be done before coating. Surfaces to be stained must clean, dry, and free of contaminants such as dirt, oil or wax. If mildew is present, clean the surface with 1 part household bleach to 10 parts water solution. New pressure-treated wood should be allowed to dry for at least 30 days. New cedar should have the mill glaze removed through sanding or an oxalic acid-based cleaning/brightener product. Discoloration can be removed and the wood restored to its natural color by using a wood brightener. Rinse well after these treatments. Wear protective gloves, clothing, and goggles when working with bleach or wood brightener. Power washing to remove old or peeling stain is recommended. Allow 2 days for wood to dry after rain, rinsing, or power washing before staining.

APPLICATION

Product is optimized for spray application, can be used in brush and roll application. Apply at air and surface temperatures above 40°F. Ideal relative humidity should be between 30% and 70%. For optimal performance, do not apply at rates higher than 8 mills wet.

CLEAN UP

Clean painting tools immediately after use with warm, soapy water. Wipe up spill before they dry with a damp cloth.

COLORS

Available in White, Black, and a range of deep colors via a tintable Accent Base.

REGULATORY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Low Lustre
Vehicle Type:	Acrylic
Weight Solids:	24-37% (varies with color)
Volume Solids:	21-27% (varies with color)
Density:	8.6-9.7 lb/gal (varies with color)
Coverage:	200-300 SF/Gallon
Dry Time:	
<i>Touch:</i>	30-45 minutes
<i>Recoat:</i>	2 hours
Clean Up:	Water
VOC:	< 50 g/L
Compliance:	As of 03/31/2026
	Federal: Yes
	OTC Phase 1: Yes
	OTC Phase 2: Yes
Primer:	Self Prime

Consult with a RepcoLite representative for additional recommendations of primers.

PRODUCT CODE INFORMATION

46871	SADDLE RIDGE EQUINE PAINT – White
46876	SADDLE RIDGE EQUINE PAINT – Accent Base
46877	SADDLE RIDGE EQUINE PAINT – Black