



Aqua-Tred

Acrylic Latex Floor Paint

Product Data Sheet

DESCRIPTION and USES

Aqua-Tred Acrylic Latex Floor Paint combines a durable, wear resistant finish and easy application with water clean up of painting tools. It can be used on concrete or wood floors, inside or outside. It is ideal for use on basement floors, patios and porches. It can also be used on concrete or bituminous tennis courts. DO NOT use this paint on garage floors. The quick dry feature of this paint allows floors to be open to light traffic in 2 to 3 hours, depending on drying conditions.

PREPARATION

Surface Preparation: All surfaces must be dry and free of dirt, grease, wax, and loose paint. Rough surfaces should be smoothed with sandpaper. All new concrete floors must be treated with a phosphoric acid based cleaning and etching product ensuring good ventilation in confined or traditionally low ventilation areas. Ensure thorough rinsing after acid treatment and allow to dry completely. Allow new concrete floors to cure 30 days before painting. Previously painted surfaces, if glossy, should be sanded to dull to assure paint adhesion.

APPLICATION

Apply with a quality paint brush or roller. Airless spray may also be used. It is important to maintain a wet edge while painting. Avoid brushing back into partially dried paint. Paint dries best between 65° to 85° F. Do not apply at temperatures below 50° F. Rough or textured surfaces will require more paint. Thinning this product is normally not necessary, however, if thinning is required use only clean water.

CLEAN UP

Clean painting tools immediately after use with warm, soapy water. Wipe up spill before they dry with a damp cloth.

SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

Available in a virtually limitless color range. Use RepcoLite's Waterborne Zero VOC Color System.

TECHNICAL DATA

Finish:	Satin Sheen
Vehicle Type:	100% Acrylic Latex
Volume Solids:	37%
Coverage:	350 – 450 SF/Gallon
Dry Time:	
<i>Touch:</i>	30 – 45 Minutes
<i>Recoat:</i>	4 Hours
Primer:	Self-Prime
VOC:	Less than 100 g/l
Clean Up:	Water

PRODUCT CODE INFORMATION

46901	Aqua-Tred—31 Base
46902	Aqua-Tred—32 Base
46903	Aqua-Tred—33 Base
46906	Aqua-Tred—36 Base

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.