



Latex Zone Marking Paint

Product Data Sheet

DESCRIPTION and USES

These paints are intended for use in marking traffic lanes on streets, parking lots, runways, etc. They provide very visible and durable line on bituminous or concrete pavement. They feature very fast dry so marked areas can quickly be returned to service. These marking paints are especially useful over new or freshly sealed bituminous pavements since tar bleed will not occur. These paints meet the requirements of Federal Specification TT-P-1952B.

SURFACE PREPARATION

Sweep or vacuum all areas to be striped to remove loose dirt. Surfaces must be oil free or have live oil spots sealed.

APPLICATION

Mix product well. Thinning of this material is not recommended, however diluting with water (not more than 10%) for use with some spray equipment may be necessary. Do not apply when rain or dew is expected within 2 hours of painting. Do not apply at temperatures below 60°F. High humidity and cool temperatures will slow the drying of these products considerably. Application to cold surfaces or cold air temperatures (less than 60°F) during drying will result in reduced paint durability. The longer these paints dry before opening painted areas to traffic, the more resistant they will be to early dirt pick-up.

SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

White, Black, Handicap Blue and Yellow.

TECHNICAL DATA

Finish:	Flat
Vehicle Type:	Vinyl/Acrylic Latex
Volume Solids:	66%
Coverage:	350 Feet of standard 4" line. (Coverage may vary with surface profile).
Dry Time:	
<i>Touch:</i>	5 – 15 Minutes (See APPLICATION)
VOC:	Less than 150 g/l
Clean Up:	Water

PRODUCT CODE INFORMATION

47210	Latex Zone Marking—White
47230	Latex Zone Marking—Handicap Blue
47260	Latex Zone Marking—Yellow
47270	Latex Zone Marking—Black

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

RepcoLite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com