

DESCRIPTION and USES

Finisher's Touch Interior Gel Stain is designed to produce rich, true colors on wood trim, cabinets, furniture, floors, and paneling. A large selection of standard colors is available, along with an almost limitless selection of special tinted colors. **Finisher's Touch Interior Gel Stain** will not raise the grain of the wood, and being a gel it allows for high loads of stain onto rags for wipe application. The gel characteristic also ensures color uniformity in-can for consistent results and a cleaner working environment.

PREPARATION

Surface Preparation: All wood surfaces to be finished must be clean, dry and free of contaminants such as oil or wax. Moisture content of wood should be 7-9%. Sand all rough or previously finished surfaces with 120 - 150 grit sandpaper. Use a tack cloth to insure a dust-free surface. Soft woods may be sealed with **Finisher's Touch Interior Softwood Sealer** for better color uniformity.

APPLICATION

Stir thoroughly before and occasionally during use. Apply generously with a brush or cloth. Allow to penetrate up to 5 minutes. Wipe off excess in the direction of the grain with a soft, absorbent cloth. **Allow 24 hours dry time before application of finish for best results.** Do not thin this product.

CLEAN UP

Clean painting tools immediately after use with specified clean up solvent.

COLORS

A full range of custom colors are available. Use RepcoLite's Alkyd Solvent-borne Color System. Maximum tint load: 12 Fl Oz per gallon.

REGULATORY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

TECHNICAL DATA

Finish:	Flat
Vehicle Type:	Alkyd Resin
Weight Solids:	36% (Varies with color)
Volume Solids:	30% (Varies with color)
Density:	7.01 lb/gal
Coverage:	500-600 square feet per gallon
Dry Time:	
<i>Touch:</i>	6 to 12 hours
<i>Recoat:</i>	24 hours
Clean Up:	Mineral Spirits
VOC:	<550 g/L
Topcoat:	Most Waterborne Clear Topcoats Most Solvent-borne Clear Topcoats

Consult with a RepcoLite representative for additional recommendations of topcoats or sealers.

PRODUCT CODE INFORMATION

49009	Interior Gel Stain
-------	--------------------

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.