

### DESCRIPTION and USES

**Finisher's Touch Interior QD Polyurethane Varnish** is a quick-drying, hard wearing clear coating designed for use on interior floors and woodwork. It is extremely durable, resisting abrasion, chemicals and water, making it suitable for use in residential or commercial settings. This quick drying version of Finisher's Touch Interior Polyurethane Varnish allows for multiple coats to be applied in a single day.

### PREPARATION

**Surface Preparation:** All wood surfaces to be finished must be clean, dry and free of contaminants such as oil or wax. Maple and birch should be sanded with 180 grit sandpaper prior to finishing. Moisture content of wood should be 7-9%. Oil-based stains should be allowed to dry a minimum of 24 hours before application of topcoat. Previously finished surfaces should be cleaned and thoroughly sanded with 220 grit sandpaper to ensure adhesion.

### APPLICATION

Apply with brush, roller or spray making sure all areas, especially edges, are well coated. Avoid application, if possible, when temperatures are above 90°F or below 50°F or when relative humidity is above 85%. Use as supplied. Do not thin.

### CLEAN UP

Clean painting tools immediately after use with specified clean up solvent.

### COLORS

Not intended for tinting.

### REGULATORY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

### TECHNICAL DATA

<b>Finish:</b>	Soft Gloss
<b>Vehicle Type:</b>	Polyurethane
<b>Weight Solids:</b>	51%
<b>Volume Solids:</b>	43%
<b>Density:</b>	7.54 lb/gal
<b>Coverage:</b>	300-500 square feet per gallon
<b>Dry Time:</b>	
<i>Touch:</i>	2 to 3 hours
<i>Recoat:</i>	4 to 6 hours
<i>Full Cure:</i>	24 hours
<b>Clean Up:</b>	Mineral Spirits
<b>VOC:</b>	<450 g/L
<b>Sealer:</b>	
<i>Wood Flooring:</i>	Self-Seal
<i>Wood (Int):</i>	Self-Seal
	49609 Finisher's Touch Sanding Sealer
	49809 Finisher's Touch Softwood Sealer
<b>Stain:</b>	
	49790 Finisher's Touch Int Penetrating Stain
	49990 Finisher's Touch Int Wiping Stain
	49009 Finisher's Touch Int Gel Stain

Consult with a RepcoLite representative for additional recommendations of sealers, stains, and glazes.

### PRODUCT CODE INFORMATION

49349 Interior QD Polyurethane Varnish

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.