

### DESCRIPTION and USES

**Finisher's Touch Sanding Sealer** is used after the staining process but before the final finish. The purpose of **Finisher's Touch Sanding Sealer** is to provide a high-building, fast-drying, and easy-sanding intermediate clear coat on interior vertical surfaces. It is not recommended for floors or other surfaces subject to heavy wear. **Finisher's Touch Sanding Sealer** does not contain zinc stearates so it may be used under urethane varnishes.

### PREPARATION

**SURFACE PREPARATION:** All wood surfaces to be finished must be clean, dry and free of contaminants such as oil or wax. Maple and birch should be sanded with 180 grit sandpaper prior to finishing. Moisture content of wood should be 7-9%. Oil-based stains should be allowed to dry a minimum of 24 hours before application of topcoat. Previously finished surfaces should be cleaned and thoroughly sanded with 220 grit sandpaper to ensure adhesion.

### APPLICATION

Apply to bare or previously stained wood with a natural bristle brush, pad applicator, or spray. Allow a minimum of 45 minutes of dry time between coats of **Finisher's Touch Sanding Sealer**. Always sand between coats using 180 grit sandpaper. Allow at least two hours of dry time before applying topcoat. Do not use lacquer or shellac as a finish coat.

### CLEAN UP

Clean tools immediately after use with specified clean up solvent. Use same clean up solvent to clean dried product off equipment.

### COLORS

Not intended for tinting.

### REGULATORY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

### TECHNICAL DATA

<b>Finish:</b>	Matte
<b>Vehicle Type:</b>	Alkyd
<b>Weight Solids:</b>	36-37%
<b>Volume Solids:</b>	29-30%
<b>Density:</b>	7.0-7.1 lb/gal
<b>Coverage:</b>	300 – 500 SF/Gallon
<b>Dry Time:</b>	
<i>Touch:</i>	30 minutes
<i>Sand/Recoat:</i>	45 minutes
<i>Topcoat:</i>	2 hours
<b>Clean Up:</b>	Mineral Spirits (Paint Thinner)
<b>VOC:</b>	<550 g/L
<b>Topcoat:</b>	Finisher's Touch Int Polyurethane Varnish
<b>Stain:</b>	49790 Finisher's Touch Int Penetrating Stain 49990 Finisher's Touch Int Wiping Stain 49009 Finisher's Touch Int Gel Stain

Consult with a RepcoLite representative for additional recommendations of sealer, stains, and glazes.

### PRODUCT CODE INFORMATION

49609	Sanding Sealer
-------	----------------

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.