

Industrial Spray/Wipe Stain Base

Product Data Sheet

DESCRIPTION and USES

This product is intended for use in a production shop setting as a tintable stain base. It dries quickly enough to be used in high throughput applications, but not so fast that it cannot be applied by cloth or pad applicator. This product is compatible with all topcoats including lacquers, varnishes and catalyzed finishes. A full range of custom colors are available. NOTE: This product is for INDUSTRIAL USE ONLY. It does not comply with VOC regulations for jobsite use.

TECHNICAL DATA

Vehicle Type: Alkyd Resin

Volume Solids: 3%

Coverage: 300 – 600 SF/Gallon

Dry Time: 15 – 30 Minutes (see application info.)

VOC: 780 g/l

Clean Up: Mineral Spirits (Paint Thinner)

or VMP Naptha.

SURFACE PREPARATION

Sand bare wood with 120-grit sandpaper.

PRODUCT CODE INFORMATION

49690 Industrial Spray/Wipe Stain Base

APPLICATION

Apply to bare wood with a natural bristle brush, cloth, pad applicator or spray. Allow a minimum of 15 minutes of dry time before application of sealer and/or topcoat. Dry times may be extended depending on depth of color desired and amount of material applied to the surface.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

RepcoLite Paints, Inc.

473 W. 17th St. Holland, MI 49423 (616) 396-1275

www.repcolite.com