

DESCRIPTION and USES

Finisher's Touch Softwood Sealer is also known as a wood conditioner and is intended for use on soft, porous woods such as pine and poplar before staining to minimize the color variations that result from stain penetrating some parts of the wood more than others.

PREPARATION

SURFACE PREPARATION: All wood surfaces to be finished must be clean, dry and free of contaminants such as oil or wax. Maple and birch should be sanded with 180 grit sandpaper prior to finishing. Moisture content of wood should be 7-9%.

APPLICATION

Apply to clean sanded wood with a cloth or a natural bristle brush, wiping off the excess. For best results, allow to dry for at least 15 minutes before applying stain. If less stain penetration is desired, re-apply.

CLEAN UP

Clean tools immediately after use with specified clean up solvent. Use same clean up solvent to clean dried product off equipment.

COLORS

Not intended for tinting.

REGULATORY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

TECHNICAL DATA

Finish:	Matte
Vehicle Type:	Alkyd
Weight Solids:	13-14%
Volume Solids:	10-11%
Density:	6.9-7.0 lb/gal
Coverage:	500 – 800 SF/Gallon
Dry Time:	
<i>Touch:</i>	5 minutes
<i>Recoat:</i>	15 minutes
Clean Up:	Mineral Spirits (Paint Thinner)
VOC:	<720 g/L
Topcoat:	Most Waterborne Clear Topcoats Most Solvent-borne Clear Topcoats
Stain:	49790 Finisher's Touch Int Penetrating Stain 49990 Finisher's Touch Int Wiping Stain 49009 Finisher's Touch Int Gel Stain

Consult with a RepcoLite representative for additional recommendations of sealer, stains, and glazes.

PRODUCT CODE INFORMATION

49809	Softwood Sealer
-------	-----------------

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.