

DESCRIPTION AND USES

Mira-Lac Pre-Catalyzed Lacquer is a product which offers the ease of application associated with lacquer coupled with performance characteristics similar to conversion varnishes. **Mira-Lac Pre-Catalyzed Lacquer** is a single component system that requires no additional catalyzation. It resists yellowing, meets or exceeds KCMA performance requirements and is recommended for use on fine furniture, interior doors and trim as well as kitchen cabinets.

SPECIFICATIONS

SURFACE PREPARATION: All wood surfaces to be finished must be clean, dry and free of contaminants. Stained surfaces should be allowed adequate dry time before finishing. To ensure coating system integrity in situations where the process involves application over existing finishes or if various brands or types of products will be used in a system, testing adhesion and compatibility on a sample panel is strongly encouraged.

MATERIAL PREPARATION: **Mira-Lac Pre-Catalyzed Lacquer** is a single component product that does not require the addition of a catalyst. It is supplied ready-for-spray and does not require thinning. Stir container contents well before use. Keep container closed when not dispensing.

APPLICATION: **Mira-Lac Pre-Catalyzed Lacquer** is designed for all types of spray application. Apply 1 coat of sealer at 3-4 mils wet film build and topcoat with 1-2 coats of **Mira-Lac Pre-Catalyzed Lacquer**. Total system film build should not exceed 3 dry mils.

CLEAN UP: Use **910 Lacquer Thinner** to clean dried product off equipment.

PRECAUTIONS

This product is intended for use by properly trained professionals in a controlled environment. Always pre-test the product or system on the substrate you will be using and under your line conditions to confirm application suitability and to avoid the need for costly refinishing.

COMPANION PRODUCTS

- 740 Series Products
- 800 Series Stains, Glazes and Toners
- 400 Series Stains and Fillers
- 910 Lacquer Thinner
- 950 Lacquer Retarder

PRODUCT CODES

743C - Clear Soft Gloss

TECHNICAL DATA

VEHICLE TYPE: Pre-Catalyzed Lacquer

VOLUME SOLIDS: 20%

WEIGHT SOLIDS: 27%

DENSITY: 7.7 lbs/gal

ACTUAL VOC: 5.00 lbs/gal

REGULATORY VOC: 660 g/L

SEALER: Self-seal OR 740 Series Sealers and Primers. See Companion Products for more information.

CLEAN UP SOLVENT: 910 Lacquer Thinner

COVERAGE: 315-330 square feet at 1 mil dry film thickness.

DRY TIME: Light sand in 30 minutes. Recoat in 45 minutes.

SHELF LIFE: 1 year shelf life when properly stored.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

RepcoLite
Quality Paint Since 1946

RepcoLite Paints, Inc.
473 W. 17th St.
Holland, MI 49423
(616) 396-1275
www.repcolite.com