

Dye Stain Reducer

Product Data Sheet

DESCRIPTION and USES

This product is intended for use in a production shop setting as a tintable dye stain base. It is used as a carrier for all solvent-reducible NGR and Irgasperse dyes. The solvent blend of this product allows for maximum color development on all species of woods. This product is compatible with all stains and topcoats including lacquers, varnishes and catalyzed wood finishes. A full range of custom colors are available. **NOTE: This product is for INDUSTRIAL USE ONLY. It does not comply with VOC regulations for jobsite use.**

TECHNICAL DATA

Volatile Content:	100%
Dry Time:	5 – 10 Minutes (see application info.)
VOC:	830 g/l
Clean Up:	Untinted 90314
	RepcoLite #75 Lacquer Thinner

SURFACE PREPARATION

Sand bare wood with 120 – 320 grit sandpaper.

PRODUCT CODE INFORMATION

90314

Dye Stain Reducer

APPLICATION

Apply to bare wood with a natural bristle brush, cloth, pad applicator or spray. Allow a minimum of 5 minutes of dry time before application of sealer and/or topcoat. Dry times may be extended depending on depth of color desired and amount of material applied to the surface.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantibility and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE. **RepcoLite Paints, Inc.** 473 W. 17th St. Holland, MI 49423 (616) 396-1275 www.repcolite.com