

DESCRIPTION AND USES

Port City Brightwork Spar Varnish is a premium quality exterior clear varnish that resists the harmful effects of sun and weather. Our formula combines natural oils, tough plastic resins, and UV light resistors to provide maximum protection from the elements. It is an ideal choice for boats, spars, oars and trim. It is also suitable for use on wood doors, patio furniture, picnic tables, and exterior woodwork.

SPECIFICATIONS

SURFACE PREPARATION: All surfaces to be coated must be dry and clean.

New Wood: Sand smooth with 120 grit or 150 grit sandpaper. Remove sanding dust. Apply at least two coats, sanding with 180 grit or 220 grit sandpaper between coats. If wood has been stained, allow at least 16 hours for the stain to dry before finishing.

Previously Finished Surfaces: Remove all wax, grease, and dirt. Sand the surface thoroughly with 150 grit sandpaper. Use a tack cloth to remove sanding dust before finishing.

Application: Stir well. Apply with a quality natural bristle brush. Allow 24 hours to dry between coats, longer if temperatures are below 65° F. Do not thin this product.

Cleanup: Clean tools and equipment immediately with Paint Thinner (Mineral Spirits)

APPLICATION: Stir well. Apply with a quality natural bristle brush. Allow 24 hours to dry between coats, longer if temperatures are below 65°F. Do not thin this product.

CLEAN UP: Clean tools and equipment immediately with Paint Thinner (Mineral Spirits).

For complete safety information, refer to the MATERIAL SAFETY DATA SHEET for this product.

PRODUCT CODES

GALLONS

00559 - Clear Gloss 00560 - Clear Satin

QUARTS

00557 - Clear Gloss 00558 - Clear Satin

TECHNICAL DATA

FINISH: Satin and Gloss

VEHICLE TYPE: Linseed/Tung

Oi

VOLUME SOLIDS: 44%

WEIGHT SOLIDS: 52%

DENSITY: 7.5 lbs/gal

VOC: 420 g/L

CLEAN UP SOLVENT: Paint

Thinner (Mineral Spirits)

COVERAGE: 450 SF/gallon

DRY TIME: Dry to touch in 4-6 hours. Re-coat in 12-16 hours on

bare wood.

SHELF LIFE: 1 year shelf life

when properly stored.

Port City Paints 1250 9th St. Muskegon, MI 49440 www.portcitypaints.com

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. Repcolite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantibility and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.